



565C1 Hotwire Air Velocity Meter

APPLICATIONS

- Air flow measurements in heating, ventilation and air conditioning systems
- Where low and high feet per minute readings are critical - you must use a hot wire below 80 feet per minute.



Comes hardwired with protective boot (A604)

Turn over for technical information and accessory part numbers.

The Value Leader™

Features

- Air flow 0.2 to 20 m/s (Also reads km/s, ft/min, knots/h, miles/h)
- Temperature -5° to 175° F (-20° to 80°C)
- Data record function for maximum and minimum temperature and air velocity reading
- Download to a computer using the RS-232 port and optional A500 cable. (The 565 uses Microsoft® Hyper Terminal to download and display air velocity and temperature on your PC.)
- 39" cable length, hard wired, telescoping tip expands from 10" to 37" (cable length decreases to 12" at full extension)
- Data Hold
- Auto Power Off
- Protective Boot Included



TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

Test Products International, Inc.

Headquarters:
9615 SW Allen Blvd.
Beaverton, OR 97005
USA
503-520-9197
Fax: 503-520-1225
email:
info@tpi-thevalueleader.com

Test Products International, Ltd.

342 Bronte St. South
Unit 9
Milton, Ontario L9T 5B7
Canada
905-693-8558
Fax: 905-693-0888
email:
info@tpicanada.com

Test Products International UK Ltd.

Longley House, East Park
Crawley, West Sussex
RH10 6AP England
Tel: +44 (0)1293 561212
Fax: +44 (0)1293813465
contactus@tpieurope.com

565 Hotwire Air Velocity Meter

SPECIFICATIONS

Display	Dual digits LCD with function annunciation
Measurement	m/s, km/s, ft/min, knots, mile/h, °C, °F
Measurement Range and Accuracy:	
Air Flow (Hot) Sensor	0.2 ~ 20 m/s ($\pm 5\%$ of reading ± 3 digits)
Temperature	-5°F ~ 175°F ($\pm 1\%$ of reading $\pm 1.0^\circ\text{F} \pm 3$ digit) -20°C ~ 80°C ($\pm 1\%$ of reading $\pm 0.5^\circ\text{C} \pm 3$ digit) <i>*Sensor: Precision glass bead thermistor</i>
Operating Temperature	0 ~ 50°C (32°F ~ 122°F)
Operating Humidity	Less than 80% R/H
Powering	1.5V AAA x 6ea
Optional Accessories	A500 RS-232 cable A910 soft shoulder strap carrying case

Distributed By:



To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com

L 565C5-0905

Copyright © 2005 Test Products International, Inc.