

Elinx™ EPSG202

Industrial High Power PoE Splitter for 10/100/1000T


- ✓ Support 10/100/1000T for PoE in and Data out
- ✓ Support Output power up to 25 W at 24 VDC
- ✓ Wide Operating Temperature (-40 to 75C)
- ✓ Power Isolation and Short circuit protection for power output
- ✓ Auto disconnect for over power voltage input
- ✓ Provides EFT protection 3000 VDC for power line
- ✓ Supports 6000 VDC Ethernet ESD protection



The Industrial Power over Ethernet Splitter receives a unified PoE signal (data and power) via UTP/STP cable, and then separates the data from the power. The power is applied to two different outputs for non PoE devices which are not compliant with the IEEE802.3af standard.

Features

- ✓ Supports 10/100/1000T for PoE in and Data out
- ✓ Power Isolation and Short circuit protection for power output
- ✓ Auto disconnection for over power voltage input
- ✓ Supports Output power up to 25W at 24VDC
- ✓ Temperature - 40C to 75C
- ✓ IP-30 Protection
- ✓ DIN Rail and Wall Mount Design
- ✓ Provides EFT protection 3,000V_{DC} for power line
- ✓ Supports 6,000 V_{DC} Ethernet ESD protection



Ordering Information

Model Number	Description
EPSG202	Industrial PoE Splitter for 10 /100/1000T High Power PoE
Accessories	
MDR-60-48	48VDC, 60W, 1.25A, DIN Mount Power Supply

Specifications
IEEE Standard Compliance

IEEE 802.3	802.3. 10Base-T Ethernet
IEEE 802.3u	100Base-TX and 100Base-FX Fast Ethernet
IEEE 802.3x	Flow Control and Back Pressure
IEEE 802.3af	Power Over Ethernet

Power

Power Output	25 Watts at 24VDC
Protection	Power Isolation, Short Circuit Protection
Power Connection	Removable Terminal Block
Wire Size	12 to 24 AWG
Power Use	30.8 Watts

Interface

Connector	Data and power in: 1 x RJ-45. Data pin 1, 2, 3, 6, 4, 5, 7, 8 Power pin: 4,5(V+) , 7,8(V-) or 1,2(V+) , 3,6(V-) Data out: 1 x RJ-45, Data pin 1, 2, 3, 6, 4, 5, 7, 8 Power out: 1x 6 pin Terminal Block
-----------	--

EFT Protection	3000 V EFT Protection
----------------	-----------------------

Environmental

Op. Temp	- 40 to 75°C (-40 to 167°F)
Storage Temp	- 40 to 85°C (-40 to 185°F)
Op. Humidity	5 to 95% (Non-condensing)

Mechanical

Enclosure	IP30 Metal Enclosure
Mounting	35mm DIN Rail or Panel Mount Attachments
Dimensions	30mm (W) x 95mm (D) x 140mm (H) 1.18 x 3.74 x 5.51 inches

ESD Protection 6000V ESD Protection

LED Indicators System Power (Green)

Specifications

Regulatory

Safety	UL / cUL 508 / CE/EN60950-1
EMC	CE EN61000-6-2 CE EN61000-6-4 CE EN61000-4-2 (ESD) CE EN61000-4-3 (RS) CE EN61000-4-4 (EFT) CE EN61000-4-6 (CS) CE EN61000-4-8 (Magnetic Field)
Free Fall Shock Vibration	IEC60068-2-32 IEC60068-2-27 IEC60068-2-6

