




REV.	REVISION	DATE



(YOKE FACE UP)



(YOKE FACE UP)

DFMM-LCLC-XX
 xxM LC/LC MM 62.5/125, DUPLEX RISER
 QTY. 1
www.bb-elec.com


DETAIL A

- NOTES:
1. INSERTION LOSS < 0,5dB.
 2. OPERATION TEMP: -20°C TO +60°C
 3. ORANGE PVC OUTER JACKET
 4. INDIVIDUALLY BAGGED AND LABELED, (SEE DETAIL A)

CHART

DFMM-LCLC-10M	10	32.8'(10000)	+2"/-0(+50/-0)	
DFMM-LCLC-5M	5	16.4'(5000)	+2"/-0(+50/-0)	
DFMM-LCLC-3M	3	9.84'(3000)	+2"/-0(+50/-0)	
DFMM-LCLC-2M	2	6.56'(2000)	+2"/-0(+50/-0)	
DFMM-LCLC-1M	1	3.28'(1000)	+2"/-0(+50/-0)	
PART NO.	XX	L	T	BARCODE

B&B Electronics Manufacturing Co.

	UNIT: Inches[mm]	TITLE: xxM DUPLEX 62.5/125 MULTIMODE LC/LC RISER JUMPER CABLE WITH CLIPS		
	DRAWN BY A. MEDINA	DATE 09/18/2008		
CHECKED BY	DATE	DRAWING NO. C.D. 2381	REV. A	
APPROVED BY	DATE	REF:		
P.O. NO.:	DATE	PART NO. DFMM-LCLC-XX		