

# MOS FET Relays

# G3VM-355J/JR

**MOS FET Relay with Both SPST-NO and SPST-NC Contacts Incorporated in a Single SOP Package.  
General-purpose (high On-resistance) Series Added.**

- SPST-NO/SPST-NC models with an 8-pin SOP package in the 350-V load voltage series.
- Continuous load current of 120 mA.
- Dielectric strength of 1,500 Vrms between I/O.
- RoHS Compliant.

## ■ Application Examples

- Broadband systems
- Measurement devices and Data loggers
- Amusement machines



**Note:** The actual product is marked differently from the image shown here.


## ■ List of Models

Contact form	Terminals	Load voltage (peak value)	Model	Number per stick	Number per tape
SPST-NO/ SPST-NC	Surface-mounting terminals	350 VAC	G3VM-355JR	50	---
			G3VM-355J		
			G3VM-355JR(TR)	---	2,500
			G3VM-355J(TR)		

## ■ Dimensions

**Note:** All units are in millimeters unless otherwise indicated.


### G3VM-355J/JR



**Note:** The actual product is marked differently from the image shown here.


## ■ Terminal Arrangement/Internal Connections (Top View)

### G3VM-355J/JR



## ■ Actual Mounting Pad Dimensions (Recommended Value, Top View)

### G3VM-355J/JR



## ■ Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Item	Symbol	Rating	Unit	Measurement conditions
Input	LED forward current	$I_F$	50	mA
	Repetitive peak LED forward current	$I_{FP}$	1	A
	LED forward current reduction rate	$\Delta I_F/\text{°C}$	-0.5	mA/°C
	LED reverse voltage	$V_R$	5	V
	Connection temperature	$T_j$	125	°C
Output	Load voltage (AC peak/DC)	$V_{OFF}$	350	V
	Continuous load current	$I_O$	120 (90)	mA
	ON current reduction rate	$\Delta I_{ON}/\text{°C}$	-1.2 (-0.9)	mA/°C
	Connection temperature	$T_j$	125	°C
Dielectric strength between input and output (See note 1.)	$V_{I-O}$	1,500	$V_{rms}$	AC for 1 min
Operating temperature	$T_a$	-40 to +85	°C	With no icing or condensation
Storage temperature	$T_{stg}$	-55 to +125	°C	With no icing or condensation
Soldering temperature (10 s)	---	260	°C	10 s

Values inside parenthesis ( ) are for G3VM-355J

## ■ Electrical Characteristics ( $T_a = 25^\circ\text{C}$ )

Item	Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
Input	LED forward voltage	$V_F$	1.0	1.15	1.3	V $I_F = 10 \text{ mA}$
	Reverse current	$I_R$	---	---	10	$\mu\text{A}$ $V_R = 5 \text{ V}$
	Capacity between terminals	$C_T$	---	30	---	pF $V = 0, f = 1 \text{ MHz}$
	Trigger LED forward current	$I_{FT}$	---	1	3	mA SPST-NO: $I_O = 120 \text{ mA}$
		$I_{FC}$				SPST-NC: $I_{OFF} = 10 \mu\text{A}$
Output	Maximum resistance with output ON	$R_{ON}$	---	15 (40)	25 (50)	Ω SPST-NO: $I_F = 5 \text{ mA}, I_O = 120 \text{ mA}$
	Current leakage when the relay is open	$I_{LEAK}$	---	0.0015 NO (0.006) 0.0105 NC (0.003)	1.0	$\mu\text{A}$ $V_{OFF} = 350 \text{ V}$
	Capacity between terminals	$C_{OFF}$	---	65 (30)	---	pF $V = 0, f = 1 \text{ MHz} (\text{NO})$ $V = 0, f = 1 \text{ MHz}, I_F = 5 \text{ mA}$ ( $\text{NC}$ )
Capacity between I/O terminals	$C_{I-O}$	---	0.8	---	pF	$f = 1 \text{ MHz}, Vs = 0 \text{ V}$
Insulation resistance	$R_{I-O}$	1,000	---	---	MΩ	$V_{I-O} = 500 \text{ VDC}$ , $R_{OH} \leq 60\%$
Turn-ON time	SPST-NO	$t_{ON}$	---	0.18 (0.3)	1.0 (1.0)	ms $I_F = 5 \text{ mA}, R_L = 200 \Omega$ , $V_{DD} = 20 \text{ V}$ (See note 2.)
	SPST-NC		---	0.15 (0.25)	1.0 (1.0)	ms
Turn-OFF time	SPST-NO	$t_{OFF}$	---	0.11 (0.15)	1.0 (1.0)	ms
	SPST-NC		---	0.7 (0.5)	3.0 (1.0)	ms

Values inside parenthesis ( ) are for G3VM-355J

## ■ Recommended Operating Conditions


Use the G3VM under the following conditions so that the Relay will operate properly.

Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	$V_{DD}$	---	---	280	V
Operating LED forward current	$I_F$	5	10	25	mA
Continuous load current (AC peak/DC)	$I_O$	---	---	120 (90)	mA
Operating temperature	$T_a$	-20	---	65	°C

Values inside parenthesis ( ) are for G3VM-355J

- Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.




- Note: 2. Turn-ON and Turn-OFF Times









## ■ Engineering Data

G3VM-355J







Common Characteristics; SPST-NO / SPST-NC



Characteristics; SPST-NO






**■ Engineering Data**  
**G3VM-355J (continued)**  
**Characteristics; SPST-NC**









## ■ Engineering Data

G3VM-355JR







### Common Characteristics; SPST-NO / SPST-NC




### Characteristics; SPST-NO



**■ Engineering Data**  
**G3VM-355JR (continued)**  
**Characteristics; SPST-NC**





All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at [http://www.components.omron.com/components/web/webfiles.nsf/sales\\_terms.html](http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html)

**ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.**

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.



**OMRON ELECTRONIC  
COMPONENTS LLC**  
55 E. Commerce Drive, Suite B  
Schaumburg, IL 60173

**847-882-2288**

Cat. No. X302-E-1

12/10

Specifications subject to change without notice

**OMRON ON-LINE**

Global - <http://www.omron.com>  
USA - <http://www.components.omron.com>

Printed in USA