


MOS FET Relays G3VM-101HR

Low 100-mΩ ON Resistance. High-power, 1.4-A Switching with a 100-V Load Voltage, SOP Package.

- Continuous load current of 1.4 A (connection C = 2.8 A).
- Dielectric strength of 1,500 Vrms between I/O.
- RoHS Compliant



■ **Application Examples**

- Broadband systems
- Measurement devices
- Data loggers
- Industrial equipment

NEW

Note: The actual product is marked differently from the image shown here.

■ **List of Models**


Contact form	Terminals	Load voltage (peak value) (See note.)	Model	Number per stick	Number per tape
SPST-NO	Surface-mounting terminals	100 V	G3VM-101HR	75	---
			G3VM-101HR(TR)	---	2,500

Note: The AC peak and DC value is given for the load voltage.


■ **Dimensions**

Note: All units are in millimeters unless otherwise indicated.

G3VM-101HR




Note: The actual product is marked differently from the image shown here.



Weight: 0.13 g


■ **Terminal Arrangement/Internal Connections (Top View)**

G3VM-101HR



■ **Actual Mounting Pad Dimensions (Recommended Value, Top View)**

G3VM-101HR




■ Absolute Maximum Ratings (Ta = 25°C)

Item		Symbol	Rating	Unit	Measurement Conditions	
Input	LED forward current	I_F	30	mA		
	LED forward current reduction rate	$\Delta I_F/^\circ\text{C}$	-0.3	mA/°C	$T_a \geq 25^\circ\text{C}$	
	LED reverse voltage	V_R	5	V		
	Connection temperature	T_J	125	°C		
Output	Load voltage (AC peak/DC)	V_{OFF}	100	V		
	Continuous load current	Connection A	I_O	1.4	A	Connection A: AC peak/DC Connection B and C: DC
		Connection B		1.4		
		Connection C		2.8		
	ON current reduction rate	Connection A	$\Delta I_O/^\circ\text{C}$	-18.7	mA/°C	$T_a \geq 50^\circ\text{C}$
		Connection B		-18.7		
		Connection C		-37.3		
Pulse on current	I_{OP}	4	A		$t=100\text{ms}$	
Connection temperature	T_J	125	°C			
Dielectric strength between input and output (See note 1.)		V_{I-O}	1,500	V_{rms}	AC for 1 min	
Operating temperature		T_a	-40 to +85	°C	With no icing or condensation	
Storage temperature		T_{stg}	-55 to +125	°C	With no icing or condensation	
Soldering temperature (10 s)		---	260	°C	10 s	

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.


Connection Diagram



■ Electrical Characteristics (Ta = 25°C)

Item		Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions	
Input	LED forward voltage	V_F	1.18	1.33	1.48	V	$I_F = 10 \text{ mA}$	
	Reverse current	I_R	---	---	10	μA	$V_R = 5 \text{ V}$	
	Capacity between terminals	C_T	---	70	---	pF	$V = 0, f = 1 \text{ MHz}$	
	Trigger LED forward current	I_{FT}	---	0.4	3	mA	$I_O = 100 \text{ mA}$	
Output	Maximum resistance with output ON	Connection A	R_{ON}	---	0.01	0.2	Ω	$I_F=5 \text{ mA}, I_O=1.4 \text{ A}, t < 1 \text{ s}$
		Connection B		---	0.05	0.1	Ω	$I_F=5 \text{ mA}, I_O=1.4 \text{ A}, t < 1 \text{ s}$
		Connection C		---	0.025	---	Ω	$I_F=5 \text{ mA}, I_O=2.8 \text{ A}, t < 1 \text{ s}$
Current leakage when the relay is open		I_{LEAK}	---	---	10	nA	$V_{OFF} = 100 \text{ V}$	
Capacity between I/O terminals		C_{I-O}	---	0.8	---	pF	$f = 1 \text{ MHz}, V_s = 0 \text{ V}$	
Insulation resistance		R_{I-O}	1,000	---	---	M Ω	$V_{I-O} = 500 \text{ VDC}, R_{oh} \leq 60\%$	
Turn-ON time		t_{ON}	---	1.0	5.0	ms	$I_F = 5 \text{ mA}, R_L = 200 \Omega, V_{DD} = 20 \text{ V}$ (See note 2.)	
Turn-OFF time		t_{OFF}	---	0.15	1.0	ms		

Note: 2. Turn-ON and Turn-OFF Times




■ Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.


Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	V_{DD}	---	---	100	V
Operating LED forward current	I_F	5	7.5	20	mA
Continuous load current (AC peak/DC)	I_O	---	---	1.1	A
Operating temperature	T_a	-20	---	65	°C

■ Engineering Data


LED forward current vs. Ambient temperature
IF - Ta




Continuous load current vs. Ambient temperature
IO - Ta




LED forward current vs. LED forward voltage
IF - VF




Continuous load current vs. On-state voltage
IO - VON




On-state resistance vs. Ambient temperature
RON - Ta




Trigger LED forward current vs. Ambient temperature
IFT - Ta




Turn ON, Turn OFF time vs. LED forward current
TON, TOFF - IF




Turn ON, Turn OFF time vs. Ambient temperature
TON, TOFF - Ta



Current leakage vs. Load voltage
ILEAK - VOFF



Output terminal capacitance COFF/COFF(ov) vs. Load voltage
COFF - VOFF



All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.
To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON[®]

**OMRON ELECTRONIC
COMPONENTS LLC**

55 E. Commerce Drive, Suite B
Schaumburg, IL 60173

847-882-2288

OMRON ON-LINE

Global - <http://www.omron.com>

USA - <http://www.components.omron.com>

Cat. No. G3VM-101HR_1 02/11

Specifications subject to change without notice

Printed in USA