


SERIES 94R

Economical, Binary Coded




FEATURES

- 10,000 Cycles of Operation
- Gold-Plated Contacts
- Sealed Contact System
- Right Angle Mount
- Octal, BCD & Hexadecimal Codes
- Standard or Complement
- RoHS Compliant



DIMENSIONS In inches (and millimeters)



SPECIFICATIONS: Series 94H and 94R

- Electrical Ratings**
- Make-and-break Current Rating:** 30 mA at 30 Vdc for 10,000 cycles of operation.
- Carrying Current Rating:** 100 mA at 50 Vdc
- Contact Resistance:** 50 mohms maximum initially (measured at 10 mA, 50 mVdc). 150 mohms maximum after life.
- Insulation Resistance:**(measured at 100 Vdc across open switch contacts) Initial: 5000 Mohms minimum. After Life: 1000 Mohms minimum.
- Dielectric Strength:** (measured across open switch contacts) Initial: 500 Vac RMS minimum. After Life: 250 Vac RMS

Mechanical Ratings

- Mechanical Life:** 10,000 cycles of operation. One cycle is a rotation through all positions and a complete return through all positions.
- Mechanical Shock:** 1000g's, 0.5 mS, half sine per MIL-STD-202F, Method 213, Test Condition E.
- Vibration Resistance:** 10-2000 Hz at 15G or 0.060" double amplitude per MIL-STD-202F, Method 204, Test Condition B.
- Operational Torque:** 2 to 6 inch-ounces initially and 1.2 inch-ounces minimum after life.

Environmental Ratings

- Operating Temperature Range:** -40° to +85°C.
- Storage Temperature Range:** -40° to +85°C.

Moisture Resistance: 240 hours with temperature cycling and polarization. Passes insulation resistance and dielectric strength per MIL-STD-202F, Method 106 following exposure.

Materials and Finishes

- Rotor and Switch Body:** Plastic (UL94V-O)
- Contact Material:** Copper alloy plated. 30 microinches minimum gold over 50 microinches minimum nickel.
- Shorting Member:** Copper alloy plated. 30 microinches minimum gold over 50 microinches minimum nickel.
- Terminals:** Copper alloy, matte tin plated over nickel barrier.

CODE & TRUTH TABLES: Series 94H and 94R

Standard Output	CODE OUTPUT				CODE OUTPUT				Complement Output
	1	2	4	8	1	2	4	8	
0					•	•	•	•	
1	•								•
2		•							•
3			•						•
4				•					•
5	•								•
6		•							•
7			•						•
8				•					•
A	•	•							•
B		•	•						•
C			•	•					•
D	•			•					•
E		•			•				•
F			•			•			•

Dot indicates terminal to common connection. All switches are continuous rotation.

Octal and Octal Complement outputs are 0 thru 7 positions.

BCD and BCD Complement outputs are 0 thru 9 positions.

Hexadecimal and Hexadecimal Complement outputs are 0 thru F positions.

Standard codes have natural color rotors; complements have rotors in a contrasting color.

Internal O-ring: Rubber BUNA-N

Soldering Information

- Soldering Temperature:** 260° C maximum.
- Cleaning:** Acceptable solutions include 1-1-1 Trichlorethane, Freon (TF, TE, or TMS), Isopropyl Alcohol and detergent (140°F maximum). Solutions which are not recommended include Acetone, Methylene Chloride, and Freon TMC.

ORDERING INFORMATION: Series 94R

Continuous Rotation Versions			
Code	No. of Positions	Standard Code Part Number	Complement Part Number
Octal	8	94RB08CT	94RC08CT
BCD	10	94RB10CT	94RC10CT
Hexadecimal	16	94RB16CT	94RC16CT
Rotational Stop Versions*			
Code	No. of Positions	Standard Code Part Number	Complement Part Number
Hexadecimal	16	94RB16FT	94RC16FT

* Consult Grayhill for 8 or 10 position