



# TRG36 SERIES 36W SWITCHING ADAPTER



## Features

- \* Universal Input Range 90-264VAC
- \* Meets EN55022 Class "B" and CISPR/FCC Class B, Conducted
- \* Continuous Short Circuit Protection
- \* Leakage Current 0.25mA Max.
- \* Over Voltage Protection
- \* Meet CEC & ErP Level V
- \* (Output cable length  $\leq$  1800mm)  
(TRG36A09: Output Cable Length  $\leq$  1220mm)  
(TRG36A05: Output Cable Length  $\leq$  720mm  
18AWG/UL2464)

## Ordering information

TRG36AXX-	XX	X	XX
Model No.	DC Plug Type	OVP	DC Cable Length and Type
		E: With OVP	01: 720mm 02: 1220mm 03: 1800mm 11: 720mm with Ferrite Core 12: 1220mm with Ferrite Core 13: 1800mm with Ferrite Core *18AWG/UL1185



MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	RIPPLE & NOISE	VOLTAGE REGULATION	LINE REGULATION	LOAD REGULATION	% EFF. (Typ.)
TRG36A05	5V	4.0A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 6\%$	73%
TRG36A09	9V	3.0A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 5\%$	77%
TRG36A12	12V	2.5A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 5\%$	78%
TRG36A13	13.5V	2.4A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 5\%$	80%
TRG36A15	15V	2.4A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 3\%$	80%
TRG36A18	18V	2.0A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 2\%$	81%
TRG36A24	24V	1.5A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 2\%$	81%
TRG36A48	48V	0.75A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 2\%$	83%

Specifications are subject to change without notice.

## Specifications

### INPUT SPECIFICATIONS:

Voltage ..... 90~264Vac  
 Frequency ..... 50 to 60Hz  
 Inrush Current ..... 60A max. @240Vac  
 Leakage Current ..... 0.25mA max.

### OUTPUT SPECIFICATIONS:

Holdup Time ..... 8ms typ. @115Vac  
 Short Circuit Protection ..... Continuous(Auto Recover)  
 Over Voltage Protection .....TVS Component to Clamp  
 Temperature Coefficient .....  $\pm 0.05\%/^{\circ}\text{C}$

### GENERAL SPECIFICATIONS:


Isolation ..... Input to output = 4,242VDC  
 Operating Temperature ..... 0 ~ 60°C (see derating curve)  
 Storage Temperature ..... -20~85°C  
 Humidity ..... 93% RH max. Non condensing  
 Cooling ..... Natural Convection  
 Switching Frequency ..... 50~70KHz  
 MTBF ..... MIL-HDBK-217F, GB, at 25°C/115VAC ..... 200K hrs min.  
 Altitude ..... 2000m  
 Dimensions ..... 4.331x1.969x0.787inches (110.00x50.00x20.00mm)  
 Weight ..... 190g(0.42 Pounds)  
 AC Inlet ..... IEC320/C8

### SAFETY AND EMC:


Emission and Immunity ..... EN55022 Class B, FCC Part 15 Class B  
 EN61000-6-3, EN61000-3-2, EN61000-3-3  
 EN55024, EN61204-3, EN61000-6-1  
 Safety ..... IEC60950-1, EN60950-1, UL60950-1

### Mechanical Specification

All Dimensions are in inches(mm)  
 Tolerance: Inches: X.XXX $\pm 0.02$   
 Millimeters: X.XX $\pm 0.5$



## TRG36 Series Derating Curve



### NOTE:

1. Voltage setpoint at 60% load
2. Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for Ripple & Noise measurement @20MHz BW.
3. Line regulation is measured from 100Vac to 240Vac, full load.
4. Load regulation measured from 60% to 100% full load and from 60% to 20% load (60% +/- 40% full load)
5. "Various TR Series adapters are PSE certified. PSE certification alone is not sufficient for importation into Japan. A valid PSE mark must contain the name of the importer as shown in the example below. If PSE mark is required, the name of the registered importer must be supplied to Cincon on order placement. Product labels will not contain PSE mark if importer name is not supplied. Consult factory or local representative for details"

