


Plug-In Directional Coupler

PDC-20-3+

50Ω 0.2 to 250 MHz



CASE STYLE: A01
PRICE: \$23.20 ea. QTY. (1-9)

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

INPUT	1
OUTPUT	4
COUPLED	3
GROUND	2,5,7,8
CASE GROUND	2,5,7,8
NOT USED	6


Features

- excellent directivity, 33 dB typ.
- low mainline loss, 0.25 dB typ.
- up to 4W power input
- good VSWR, 1.2:1 typ.
- rugged welded construction, hermetically sealed

Applications

- HF/VHF
- defense & federal communications
- power levelling

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	H	J	K	wt	
.200	.20	.14	.031	grams	
5.08	5.08	3.56	0.79	5.2	

Directional Coupler Electrical Specifications

FREQ. (MHz)	COUPLING (dB)		MAINLINE LOSS** (dB)						DIRECTIVITY (dB)						VSWR (:1)	POWER INPUT, W		
	Nom.	Flatness	L		M		U		L		M		U			Typ.	Max.	Max.
			Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.				
0.2-250	19.5±0.5	±0.5	0.35	0.6	0.25	0.5	0.35	0.6	36	30	33	25	25	20	1.2	1.5	4.0	

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]


1. Mainline loss includes theoretical power loss at coupled port.

* Insertion loss specification in L range may degrade up to 1 dB at cold temperature, -55°C


Typical Performance Data

Frequency (MHz)	Mainline Loss (dB) In-Out	Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
				In	Out	Cpl
0.20	0.29	19.42	39.65	22.30	21.91	21.73
0.60	0.30	19.43	39.51	28.91	27.26	28.15
1.00	0.27	19.39	39.77	30.93	28.75	30.08
9.00	0.21	19.33	40.19	40.70	34.16	39.85
26.00	0.21	19.34	41.15	40.44	34.09	40.06
81.00	0.24	19.35	46.36	35.00	32.30	36.98
128.00	0.25	19.36	48.96	31.81	30.48	33.86
151.00	0.25	19.34	43.44	30.66	29.73	32.37
206.00	0.27	19.37	34.46	28.27	27.91	28.82
250.00	0.28	19.40	29.83	27.05	26.87	26.10


PDC-20-3+
MAINLINE LOSS




PDC-20-3+
COUPLING & DIRECTIVITY



PDC-20-3+
RETURN LOSS



Electrical Schematic



* ELECTRICAL SCHEMATIC IS FOR DIRECTIONAL COUPLER WITH INTERNAL TRANSFORMERS THAT ROUTES DC FROM RF PORTS TO GROUND.

Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

REV. C
M119986
PDC-20-3+
WZ/TD/CP/AM
130114

