



MECHANICAL DATA



DK

PIN 1 SOURCE (COMMON) PIN 2 DRAIN 1
 PIN 3 DRAIN 2 PIN 4 GATE 2
 PIN 5 GATE 1

| DIM | mm | Tol. | Inches | Tol. |
|-----|-------|------|--------|-------|
| A | 6.45 | 0.13 | 0.254 | 0.005 |
| B | 1.65R | 0.13 | 0.065R | 0.005 |
| C | 45° | 5° | 45° | 5° |
| D | 16.51 | 0.76 | 0.650 | 0.03 |
| E | 6.47 | 0.13 | 0.255 | 0.005 |
| F | 18.41 | 0.13 | 0.725 | 0.005 |
| G | 1.52 | 0.13 | 0.060 | 0.005 |
| H | 4.82 | 0.25 | 0.190 | 0.010 |
| I | 24.76 | 0.13 | 0.975 | 0.005 |
| J | 1.52 | 0.13 | 0.060 | 0.005 |
| K | 0.81R | 0.13 | 0.032R | 0.005 |
| M | 0.13 | 0.02 | 0.005 | 0.001 |
| N | 2.16 | 0.13 | 0.085 | 0.005 |

**GOLD METALLISED
 MULTI-PURPOSE SILICON
 DMOS RF FET
 125W – 28V – 400MHz
 PUSH-PULL**

FEATURES

- SIMPLIFIED AMPLIFIER DESIGN
- SUITABLE FOR BROAD BAND APPLICATIONS
- LOW C_{rss}
- SIMPLE BIAS CIRCUITS
- LOW NOISE
- HIGH GAIN – 13 dB MINIMUM

APPLICATIONS

- HF/VHF/UHF COMMUNICATIONS
 from 1 MHz to 400 MHz

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

| | | |
|--------------|--|-------------------------|
| P_D | Power Dissipation | 350W |
| BV_{DSS} | Drain – Source Breakdown Voltage * | 70V |
| BV_{GSS} | Gate – Source Breakdown Voltage * | $\pm 20V$ |
| $I_{D(sat)}$ | Drain Current * | 20A |
| T_{stg} | Storage Temperature | -65 to $150^{\circ}C$ |
| T_j | Maximum Operating Junction Temperature | $200^{\circ}C$ |

* Per Side

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.

ELECTRICAL CHARACTERISTICS (T_{case} = 25° C unless otherwise stated)

| Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|---------------------|---------------------------------|-----------------------|-----------------------------------|------|--------|
| PER SIDE | | | | | |
| B _V DSS | Drain–Source Breakdown Voltage | V _{GS} = 0 | I _D = 100mA | 70 | V |
| I _D DSS | Zero Gate Voltage Drain Current | V _{DS} = 28V | V _{GS} = 0 | | 4 mA |
| I _G DSS | Gate Leakage Current | V _{GS} = 20V | V _{DS} = 0 | | 1 μA |
| V _{GS(th)} | Gate Threshold Voltage * | I _D = 10mA | V _{DS} = V _{GS} | 1 | 7 V |
| g _{fs} | Forward Transconductance * | V _{DS} = 10V | I _D = 4A | 3.2 | S |
| TOTAL DEVICE | | | | | |
| G _{PS} | Common Source Power Gain | P _O = 125W | | 13 | dB |
| η | Drain Efficiency | V _{DS} = 28V | I _{DQ} = 1.6A | 50 | % |
| VSWR | Load Mismatch Tolerance | f = 400MHz | | 20:1 | — |
| PER SIDE | | | | | |
| C _{iss} | Input Capacitance | V _{DS} = 28V | V _{GS} = -5V f = 1MHz | | 240 pF |
| C _{oss} | Output Capacitance | V _{DS} = 28V | V _{GS} = 0 f = 1MHz | | 120 pF |
| C _{rss} | Reverse Transfer Capacitance | V _{DS} = 28V | V _{GS} = 0 f = 1MHz | | 10 pF |

* Pulse Test: Pulse Duration = 300 μs , Duty Cycle ≤ 2%

HAZARDOUS MATERIAL WARNING

The ceramic portion of the device between leads and metal flange is beryllium oxide. Beryllium oxide dust is highly toxic and care must be taken during handling and mounting to avoid damage to this area.

THESE DEVICES MUST NEVER BE THROWN AWAY WITH GENERAL INDUSTRIAL OR DOMESTIC WASTE.

THERMAL DATA

| | | |
|-----------------------|------------------------------------|-----------------|
| R _{THj-case} | Thermal Resistance Junction – Case | Max. 0.5° C / W |
|-----------------------|------------------------------------|-----------------|

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.




Figure 1.
Power Output and Efficiency vs. Input Power




Figure 2.
Power Output and Gain vs. Input Power




Figure 3
IMD vs. Power Output




Figure 4 – Typical IV Characteristics.







Figure 5 – Typical CV Characteristics.

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.



Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.



400MHz Test Fixture

- T1 11cm 50 Ohm UT47 semi-rigid coax on Siemens B62152A1X1 2 hole ferrite core
- T2,3,4,5 9cm 15 Ohm UT85-15 semi-rigid coax
- T6 9.7cm 50 Ohm UT85 semi-rigid coax

- L1 7 Turns 19swg enamelled copper wire 3.5mm internal diameter
- L2 5.5 Turns 19swg enamelled copper wire on Fair-rite FT50 ferrite core

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.