




- Square cap
- Designed for foil overlay
- 15 mm x 15 mm
- h = 12.5 mm
- Material: ABS/polycarbonate
- Temp. Range: -40/+85°C
- Panel cut-out: 1YS-16 x 16


All dimensions in mm

### DIMENSIONS

#### TH + 1YS




#### SMD + 1YS




### RECOMMENDED PLACEMENT OF LEDS

#### SMD



#### TH



#### LED Recommendation

SMD: 1206 - 0805 - 0603 - 0402

TH: 3 mm - Ø max 3.2 - Height max 6.5 mm

### HOW TO ORDER

#### Switch

5 E

#### Mounting



TH9 through-hole  
SH9 surface mount

#### Actuation force




20  
20Q  
35  
65

+

#### Cap

1 Y S 0 6 1 6

1YS0616 white cap with frosted white lens




A: We recommend you to allocate enough space for travel of the foil and leave the area free from adhesive. Switch travel = 1 mm.

H: The height recommendation does not include the foil. We recommend embossing the foil to follow the curve of the keycap.

The best tactile feeling is obtained with a small pretravel.

The dimension H is based on an embossed foil. With a flat foil the dimension "H" will have to be adjusted, and enough area between the cap and front panel needs to be addressed to ensure foil flexibility.



Ordering example: 5ESH935+1YS0616

Please see colour codes, updates of products and changes of specifications on [www.mec.dk](http://www.mec.dk)