Product Configuration System

Crystal Oscillators - SPXO

SG-615	P	CW	66.6667M	C	3	:	PURE SN

Oscillator Package Type
531: 8 pin plastic DIP
615: 4 pin "J" lead SMD
636: 4 pin "J" lead mini SMD
645: Plastic 5x7mm

Version
P: Output Enable
S: Standby Function

Function Description
HW: 5.0V CMOS
TW: 5.0V TTL
CW: 3.3V CMOS

Frequency
5V, HW/TW
SG-531 B Stability 55.0001~66.666MHz
SG-531 C Stability 55.0001~135MHz
SG-615 B Stability 55.0001~66.666MHz
SG-615 C Stability 55.0001~135MHz
SG-636 B Stability 32.0001~39.9999MHz
SG-636 C Stability 32.0001~135MHz
SG-645 B Stability 32.0001~39.9999MHz
SG-645 C Stability 32.0001~135MHz
3.3V, CW
SG-531 B/C/M Stability 55.0001~135MHz
SG-615 B/C/M Stability 26.0001~135MHz
SG-636 B/C Stability 32.0001~135MHz
SG-645 B/C/M Stability 32.0001~135MHz

Tape & Reel Qty
Blank: Bulk
0: 1000pcs per reel
3: 250pcs per reel

(Except SG-51/531)
SG-51/531 Series
Blank: Stick 25/35

PURE SN
ROHS
Blank = Not RoHs Compliant

Frequency Tolerance
B: +/-50ppm / -20 to +70C
C: +/-100ppm / -20 to +70C

M: +/-100ppm/-40~+85C
Available in 3.3V to 135MHz, SG-51/531 & SG-615
(NOT available in SG-636)

These packages also available in our SG-8002 programmable series.

EPSON