# QuickCarrier<sup>™</sup> USB-D



**USB** Cellular Modems

The QuickCarrier™ USB-D is a cellular dongle designed and built for M2M (machine-to-machine) applications. That means it is built for long life while delivering reliable data connectivity. The QuickCarrier USB-D is designed for quick implementation of cellular technology – allowing customers to easily connect their devices to the internet.

#### **Features**

- 3G GSM and CDMA models available
- · Internal antenna
- Short Message Services (SMS)
- · Drivers for Windows and Linux
- AT command compatible
- · Certified and Carrier approved
- Two-year warranty



## **Benefits**

- Quick deployments to shorten time to market
- Long and stable life cycles
- Certified and Carrier approved



# **Specifications**

Model

	meti (ccio)		
		Multi	
Todatal Cartifortion			
Technical Specifications	LICDA	E/D0	
Performance	HSPA+	EV-DO	
Frequency Band	3G: Penta-band 850/900/1700/1900/2100 MHz 2G: Quad-band 850/900/1800/1900 MHz	Dual-band 800/1900 MHz	
Packet Data*	HSDPA data service of up to 21.0 Mbps HSUPA data service of up to 5.76 Mbps	Data service of up to 3.1 Mbps downlink and 1.8 Mbps uplink	
Circuit Switched Data	Not Supported	Not Supported	
SMS	Point-to-Point Messaging, Mobile-Terminated SMS, Mobile-Originated SMS		
USB	USB 2.0 High Speed Compatible		
TCP/IP Functions	TCP/UDP/FTP/SMTP		
Input Power	Via USB Bus		
Connectors			
SIM Connector	Standard 1.8 and 3V SIM receptacle	NA	
Physical Description			
Physical Dimensions (L $\times$ W $\times$ H)	3.01" x 1.58" x 0.74" (7.65 cm x 4.01 cm x 1.88 cm)		
Environmental			
Operating Temperature**	-40° to +122° F (-40° to +50° C)		
Storage Temperature	-40° to +185° F (-40° to +85° C)		
Humidity	Relative humidity 20% to 90% noncondensing		
Certifications			
EMC Compliance	FCC Part 15 Class B, IC, EN301 489-1, EN301 489-7, EN301 489-24	FCC Part 15 Class B	
Radio Compliance	FCC Part 22, 24, 27, RSS 132, 133, 139; R&TTE	FCC Part 22, 24, 27	
Safety	UL60950-1, cUL60950-1, IEC60950-1	UL60950-1	
Network	PTCRB, AT&T, T-Mobile, Rogers (Bell & Telus pending)	Verizon (Sprint & Aeris pending)	

MTD-EV3

MTD-H5

<sup>\*</sup> Actual performance speeds may be affected by a variety of attributes such as cell tower distance, data loads, packet sizes, etc.

<sup>\*\*</sup> UL Listed @ 40° C, limited by power supply. UL Certification does not apply or extend to an ambient above 40° C and has not been evaluated by UL for ambient greater that 40° C. "UL has evaluated this device for use in ordinary locations only. Installation in a vehicle or other outdoor locations has not been evaluated by UL. UL Certification does not apply or extend to use in vehicles or outdoor applications or in ambient above 40° C." (Note applicable to models that include power supply only)

### **Highlights**

#### **Applications**

With 2G or 3G packet data rates, the QuickCarrier USB-D will support highly data-intensive applications such as remote video surveillance, multimedia POS/ATM terminals as well as other lower data rate applications.

#### M2M Design

The QuickCarrier USB-D is specifically designed for M2M customers. Many cellular dongles available today are designed and built with consumers in mind. Consequently, the modem is constantly undergoing change. For M2M applications this is extremely troublesome. The QuickCarrier USB-D delivers reliable 3G connectivity in a platform customers can depend on.

## **Ordering Information**

#### **GSM Products**

Product	Description	Bundle Available	Region
MTD-H5	HSPA+ USB Modem	No	Global
CDMA Product	ts		
Product	Description	Bundle Available	Region
MTD-EV3-N3	EV-DO USB Modem - for Verizon Wireless Networks	No	US

Use ordering codes for specific build options. Go to www.multitech.com for detailed product model numbers

#### Services & Warranty

Multi-Tech's comprehensive Support
Services programs offer a full array of
options to suit your specific needs. These
services are aimed at protecting your
investment, extending the life of your
solution or product, and reducing total
cost of ownership. Our seasoned technical
experts, with an average tenure of more
than 10 years, can walk you through smooth
installations, troubleshoot issues and help
you with configurations. Products include a
2-year warranty that can be extended up to
5 years via Multi-Tech's Extended Warranty
program, which offers the convenience of
Overnight Service\* for optimal uptime.

# **Extended Warranty & Overnight Services**

To give you peace-of-mind and protect your investment, our Extended Warranty Service Plans ensure your Multi-Tech products are covered for 1, 2, or 3 years beyond the manufacturer's warranty with an optional Overnight Service plan\*.

#### **Installation Support**

Multi-Tech's Installation Support Service delivers priority service with the ability to work one-on-one with an experienced Multi-Tech technical support engineer, to guide you through the installation process for our products.

#### **Technical Support Services**

At Multi-Tech, we're committed to providing you personalized attention and quality service while providing you a quick response to your product support needs. We have several options of support for you to choose from.

For additional information on Support Services as well as other service offerings, please contact your Multi-Tech representative or visit www.multitech.com/support.go.

\* Overnight replacement service is currently available for U.S. customers.

#### World Headquarters

Multi-Tech Systems, Inc. 2205 Woodale Drive Mounds View, MN 55112 U.S.A. Tel: 763-785-3500 Toll-Free: 800-328-9717 Email: sales@multitech.com www.multitech.com

#### **EMEA Headquarters**

Multi-Tech Systems (EMEA) Unit 1, Thames Court 2 Richfield Avenue Reading, Berkshire RG1 8EQ United Kingdom Tel: +(44) 118 959 7774 Email: sales@multitech.co.uk

