



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

|   |      |       |
|---|------|-------|
| D:  | 37.0 | ± max |
| T:  | 10.0 | ± max |
| Lead Diameter                             | 2.5  | ± nom |
| S:  | 19.0 | ± nom |
| L:  | 39.0 | ± nom |
| Coating Lead Run Down<br>(straight Leads) | 7.0  | ± max |
| B:  |      | ±     |
| C:  | 7.50 | ± nom |



**Electrical Specifications**

|                                       |        |       |        |
|---------------------------------------|--------|-------|--------|
| Resistance:                           | 3.0    | Ω     | ± 25 % |
| Max Steady State Current upto 65°C:   | 30.00  | A     |        |
| Max Rec. Energy Rating:               | 750    | J     |        |
| Actual Failure Instantaneous Energy:  | 1250   | J     |        |
| Maximum Capacitance @ 120 VAC:        | 51,600 | µf    |        |
| Maximum Capacitance @ 240 VAC:        | 13,024 | µf    |        |
| Maximum Capacitance @ 440 VAC:        | 3,010  | µf    |        |
| Maximum Capacitance @ 680 VAC:        | 1,500  | µf    |        |
| Resistance @ 100% Max Current:        | 0.03   | Ω     |        |
| Resistance @ 50% Max Current:         | 0.07   | Ω     |        |
| Body Temperature at 100% Max Current: | 215.00 | °C    |        |
| Dissipation Constant:                 | 78.0   | mW/°C |        |
| Thermal Time Constant:                | 240    | Sec.  |        |
| Material Type (for Beta and Curve):   | C      |       |        |

| <b>MS35 3R030</b>  |                          |
|--|--------------------------|
| Date: 11/11/2008   | Drawn by: Erin Landis    |
| Ametherm, Inc.<br>3111 N. Deer Run Road<br>Carson City, Nevada USA 89701<br>www.ametherm.com | Approved By: Mehdi Samii |
|  | Revision: A              |