



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	22.0	± max
	T:	5.0	± max
	Lead Diameter	1.0	± nom
	S:	7.8	± nom
	L:	38.0	± nom
	Coating Lead Run Down (straight Leads)	5.0	± max
	B:	9.20	± nom
	C:	3.65	± nom



Electrical Specifications

	Resistance:	14.0 Ω	± 25 %
	Max Steady State Current upto 65°C:	5.00	A
	Max Rec. Energy Rating:	75	J
	Actual Failure Instantaneous Energy:	200	J
	Maximum Capacitance @ 120 VAC:	5,209	µf
	Maximum Capacitance @ 240 VAC:	1,302	µf
	Resistance @ 100% Max Current:	0.12	Ω
	Resistance @ 50% Max Current:	0.29	Ω
	Body Temperature at 100% Max Current:	177.00	°c
	Dissipation Constant:	32.4	mw/°c
	Thermal Time Constant:	94	Sec.
	Material Type (for Beta and Curve):	H	

SL22 14005	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a