



**MATERIALS:**

HOUSING AND ROCKER: NYLON 6/6 85°C MATERIAL  
TERMINAL AND MOVING CONTACT: COPPER ALLOY

**RATINGS:**

16A. 125V.A.C. 12A. 250V.A.C.  
3/4 H.P. 125-250V.A.C.  
12 (6)A. 250 ~ VDE

**OPERATING TEMPERATURE/HUMIDITY:** -30C - 85C/100 Hour Soak @ 95% RH and 50C and 1 Hour dry in ambient = > 10 M ohms

**ELECTRICAL CYCLES:** UL Rated 6K Cycles, VDE 10K Cycles

**MECHANICAL CYCLES:** 100K Cycles

**FLAMMABILITY RATING:** UL 94V - 2

**REGULATORY APPROVALS:** UL 1054/VDE EN61058/CSA C22.2 No. 55

1	2	3	4	5	6	7	8	9	10
---	---	---	---	---	---	---	---	---	----

B-FORMAT 2002	<b>REVISIONS</b>	O	RELEASED: DGW 10-26-2009
		OCT 26 2009	

PDF File Made	<p>Southampton, Pa. 18966</p> <p>TOLERANCES UNLESS OTHERWISE SPECIFIED</p> <table border="1"> <tr> <td>2 Place Decimal ±.010</td> <td>METRIC</td> </tr> <tr> <td>3 Place Decimal ±.005</td> <td>1 Place Dec. ±.25mm</td> </tr> <tr> <td>Angles ..... ±1°</td> <td>2 Place Dec. ±.13mm</td> </tr> </table>	2 Place Decimal ±.010	METRIC	3 Place Decimal ±.005	1 Place Dec. ±.25mm	Angles ..... ±1°	2 Place Dec. ±.13mm	<p>Title: <b>SWITCH ASSEMBLY PUSH ON/OFF S.P.- S.T.</b></p>	
		2 Place Decimal ±.010	METRIC						
	3 Place Decimal ±.005	1 Place Dec. ±.25mm							
	Angles ..... ±1°	2 Place Dec. ±.13mm							
Made for: CW IND.	Division: <b>SWITCH</b>								
Drawn by: DGW 10-26-2009	Dwg. No. <b>GRSN-2011-2002</b>								
Checked by: <i>G. Guld 10-26-09</i>	Approval: <i>G. Guld 10-26-09</i>								

**MASTER**