


NS12565T101MNV



■ Features

- Item Summary
100 μH(±20%), 2.23A, 1.81A
- Lifecycle Stage
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)
Taping 2000pcs(500pcs*4reel)

■ Products characteristics table

CaseSize (EIA/JIS)	-/12565
Inductance	100 μH(±20%)
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	2.23A
Rated Current -Temperature Rise Current	1.81A
DC Resistance (max)	0.1476Ω
Avg. of DC.Resistance	0.123Ω
Temperature Range	-40°C to 125°C
Self-resonant Frequency (min)	5.5MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow


■ External Dimensions

L	12.5mm ±0.3
W	12.5mm ±0.3
H	6.5mm ±0.35

■ Recommended Land Patterns

【推奨ランドパターン】
実装上の注意
・実装状態を確認の上ご使用ください。また、ご購入の際は、本製品のハンダ付けはリフローハンダ工法に限りません。

【Recommended Land Patterns】
Surface Mounting
・Mounting and soldering conditions should be checked beforehand.
・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NS series)			
Type	A	B	C
NS 10145	2.5	5.6	3.2
NS 10155	2.5	5.6	3.2
NS 10165	2.5	5.6	3.2
NS 12555	2.5	8.6	3.2
NS 12565	2.5	8.6	3.2
NS 12575	2.5	8.6	3.2

unit:mm