

TABLE 2			
STACK HEIGHT			
SEAM LEAD STYLE	SEAF LEAD STYLE		
	-05.0	-06.0	-06.5
-02.0	7mm	8mm	8.5mm
-03.0	8mm	9mm	9.5mm
-03.5	8.5mm	9.5mm	10mm

TABLE 12	
LEAD STYLE	"T"
-02.0	.1790 [4.547]
-03.0	.2180 [5.537]
-03.5	.2380 [6.045]
**-.06.5	.3675 [9.081]
-.07.0	.3750 [9.525]
-.09.0	.4540 [11.532]
-.11.0	.5330 [13.538]
*-.13.0	.6120 [15.545]

TABLE 1			
STYLE	"J"	BODY CALLOUT	TERMINAL
-02.0	0.181 [4.60]	SEAM-XX-02.0-XX-X	SUB-T-1M36-02.0-X-X
-03.0	0.220 [5.59]	SEAM-XX-03.0-XX-X	SUB-T-1M36-03.0-X-X
-03.5	0.240 [6.10]	SEAM-XX-03.5-XX-X	SUB-T-1M36-03.5-X-X

TABLE 3				
No. OF POS	"A"	"B"	"C"	"D"
***-10	.696[17.68]	.450[11.43]	.622[15.80]	.450[11.43]
****-15	.946[24.03]	.700[17.78]	.872[22.15]	.700[17.78]
****-19	1.146[29.11]	.900[22.86]	1.072[27.23]	.900[22.86]
-20	1.196 [30.38]	.950 [24.13]	1.122 [28.50]	.950 [24.13]
*****-25	1.446[36.73]	1.200[30.48]	1.372[34.85]	1.200[30.48]
-30	1.696 [43.08]	1.450 [36.83]	1.622 [41.20]	1.450 [36.83]
-40	2.196 [55.78]	1.950 [49.53]	2.122 [53.90]	1.950 [49.53]
-50	2.696 [68.48]	2.450 [62.23]	2.622 [66.60]	2.450 [62.23]

TABLE 4				
No. OF ROWS	"E"	"F"	"G"	"H"
-04	.278[7.06]	.152[3.86]	.100[2.54]	.050[1.27]
-05, -06	.378 [9.60]	.252 [6.40]	.100 [2.54]	.050 [1.27]
-08	.478 [12.14]	.352 [8.94]	.200 [5.08]	.100 [2.54]
-10	.578 [14.68]	.452 [11.48]	.300 [7.62]	.150 [3.81]



TABLE 13			
LEAD STYLE	"U"		
	10-30 POS.	40 POS.	50 POS.
-02.0, -03.0,			
-03.5, **-.06.5, -07.0,	.006 [0.152]	.009 [0.229]	.009 [0.229]
-09.0, *-.13.0			
-11.0	.0085 [0.216]	.009 [0.229]	.009 [0.229]