


GU256X64C-3900B

SIMPLIFIED DATASHEET

■ Features

Compact size, high resolution VFD model. Recommended for devices where wide space is not available.

■ Physical dimension



Get full specification



Click here to go to request form.

Specifications

■ Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Power supply voltage	VCC	4.75	5.00	5.25	VDC	

■ Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Parallel I/F						
Logic input current	IpIH	-	-	1.0	μADC	-
D0-D7 /WR	IpIL	-	-	-200	μADC	-
Logic input voltage	VpIH	0.8VCC	-	VCC	VDC	-
D0-D7 /WR	VpIL	0	-	0.2VCC	VDC	-
Logic output voltage	VpOH	3.5	-	VCC	VDC	IOH=-10 μA
RDY	VpOL	0	-	0.6	VDC	IOL=4mA
RS-232 I/F						
Logic input voltage	VsIH	3	-	15	VDC	-
RXD, DSR	VsIL	-15	-	-3	VDC	-
Logic output voltage	VsOH	5	-	-	VDC	RL=3KΩ
RXD, DSR	VsOL	-	-	-5	VDC	-
Logic input Impedance	RsiN	3	-	7	KΩ	-
General-purpose I/O port						
Power Supply Current 1	ICC1	-	0.43	0.56	ADC	All dots ON
Power Supply Current 2	ICC2	-	0.33	0.43	ADC	All dots OFF
Power Supply Current 3	ICC3	-	80	120	mADC	Display power OFF
Power Consumption	-	-	2.15	2.80	W	All dots ON

■ Optical Specifications

Parameter	Value
Luminance	250 cd/m ² Min. (500 cd/m ² Typ.)
Color of illumination	Green (Blue-Green)

■ Environmental Specifications

Parameter	Value
Operating Temperature	-40 ~ +85 degrees celsius
Storage Temperature	-40 ~ +85 degrees celsius
Operating Humidity	20 ~ 80% R.H. (non-condensing)
Vibration (non-operating)	10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z
Shock (non-operating)	392m/s ² (40G) 9ms X-Y-Z, 3 times each direction

■ Physical Specifications

Parameter	Value
Number of Dots	16,384 (256 x 64)
Display Area	83.08 mm x 20.68 mm
Dot Size (X x Y)	0.2 mm x 0.2 mm
Dot Pitch (X x Y)	0.325 mm x 0.325 mm
Weight	About 65 g

■ Interface

Parallel(CMOS), Asynchronous Serial (RS232), I/O port

■ Pin Assignment

Pin No.	Signal	Pin No.	Signal
1	D7	2	D6
3	D5	4	D4
5	D3	6	D2
7	D1	8	D0
9	GND	10	/WR
11	GND	12	RDY
13	GND	14	GND
15	VCC	16	VCC

(Asynchronous Serial)

Pin No.	Signal	Baud Rate Setting
1	RXD	4800bps
2	DTR	9600bps
3	DSR	19200bps
4	TXD	38400bps*
5	TEST	57600bps
6	VCC	115200bps
7	GND	(*:Default setting)

(General-purpose I/O port: Abbreviation)

■ Selectable Font

Parameter	Value
ASCII, KANA	All Font Size
International	6 x 8 / 8 x 16 / 12 x 24 / 16 x 32 dot
2-byte character	16 x 16 dot
Japanese	32 x 32 dot
Character numbers	42 x 8 by 6 x 8 dot ASCII
	21 x 2 by 12 x 24 dot ASCII
	16 x 4 by 16 x 16 dot 2-byte character
	8 x 2 by 32 x 32 dot Japanese

■ Functions

Parameter	Value
Variable Character display	Variable Action Commands
Scroll function	Line / BOX Draw
Display Power Auto ON/OFF	AND/OR/XOR Mixture display
User Windows function	Program Macro function
I/O Port Control Function	Graphic DMA mode
Bit image by dot	
Variable stored settings	
etc.	



Leaflet contents, and specifications and external appearance of products, may change without notice.

Please confirm product details in the specification.

(C) Copyright NORITAKE ITRON CORP.