


GU256X64D-7000

SIMPLIFIED DATASHEET

Features

256x64 dots, with display area width twice that of GU128X64D-7000. Simultaneously display lots of information, ranging from images to numerical data.

Physical dimension



Get full specification



Click here to go to request form.

Specifications

Electrical Ratings

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Condition |
|----------------------|--------|------|------|------|------|-----------|
| Power supply voltage | VCC | 4.75 | 5.00 | 5.25 | VDC | - |

Electrical Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Condition |
|-------------------------|--------|--------|------|--------|--------|-------------------|
| 'L' Logic Input Current | | | | | | |
| D0-D7,/WR,/RD | IIL1 | - | - | -0.15 | mA | VIN=0V |
| /RESET | IIL2 | - | - | -0.6 | mA | VIN=0V |
| 'H' Logic Input Current | | | | | | |
| D0-D7,/WR,/RD,/RESET | IIH | - | - | 1.0 | μADC | VIN=5V |
| Logic Input Voltage | VIH | 0.8VCC | - | VCC | VDC | - |
| D0-D7,/WR,/RD,/RESET | VIL | 0 | - | 0.2VCC | VDC | - |
| Logic Output Voltage | VOH | 3.8 | - | VCC | VDC | IOH=-1.5mA |
| D7(Busy flag), PBUSY | VOL | 0 | - | 0.6 | VDC | IOL=1.6mA |
| Logic input resistance | | | | | | |
| SIN | RIN | 3 | - | - | KΩ | - |
| Logic Input Voltage | | | | | | |
| SIN | VIH | 3.0 | - | +15 | VDC | - |
| SIN | VIL | -15 | - | 0.5 | VDC | - |
| Logic Output Voltage | | | | | | |
| VOH | 4.0 | - | VCC | VDC | RL=3KΩ | - |
| SBUSY | VOL | 0 | - | 0.5 | VDC | RL=3KΩ |
| Power Supply Current 1 | ICC-1 | - | 760 | 950 | ADC | All dots ON |
| Power Supply Current 2 | ICC-2 | - | 570 | 710 | ADC | All dots OFF |
| Power Supply Current 3 | ICC-3 | - | 30 | 40 | mADC | Display power OFF |
| Power Consumption | | - | 3.8 | 4.75 | W | All dots ON |

Optical Specifications

| Parameter | |
|-----------------------|---------------------------------------------------------|
| Number of Dots | 16,384 (256 x 64) |
| Character numbers | 36 x 8 / Max42 x 8 by 5 x 7 dot ANK |
| Display Area | 115.05mm x 28.65 mm |
| Dot Size (X x Y) | 0.30 mm x 0.30 mm |
| Dot Pitch (X x Y) | 0.45 mm x 0.45 mm |
| Luminance | 350 cd/m ² Min. (700 cd/m ² Typ.) |
| Color of illumination | Green (Blue-Green) |

Environmental Specifications

| Parameter | |
|---------------------------|-------------------------------------------------------------|
| Operating Temperature | -40 ~ +85 degrees celsius |
| Storage Temperature | -40 ~ +85 degrees celsius |
| Operating Humidity | 20 ~ 80% R.H. (non-condensing) |
| Storage Humidity | 20 ~ 80% R.H. (non-condensing) |
| Vibration (non-operating) | 10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z |
| Shock (non-operating) | 392m/s ² (40G) 9ms X-Y-Z, 3 times each direction |

Character display

| Parameter | |
|---------------------|-----------------------------------------|
| Number of Dots | 256 x 64 dots |
| Character font type | 5 x 7 ANK, International font |
| Character width | Fixed/Proportional character format 1&2 |
| Attribution | Character magnify, Reverse |
| Weight | About 122 g |

Interface

Parallel(CMOS), Asynchronous Serial (RS232)

Pin Assignment (Parallel)

| Pin No. | Signal | Pin No. | Signal |
|---------|--------|---------|-----------|
| 1 | GND | 2 | Vcc |
| 3 | NC | 4 | RS |
| 5 | /WR | 6 | /RD |
| 7 | D0 | 8 | D1 |
| 9 | D2 | 10 | D3 |
| 11 | D4 | 12 | D5 |
| 13 | D6 | 14 | D7(PBUSY) |

(Asynchronous Serial)

| Pin No. | Signal | Baud Rate Setting |
|---------|--------|---------------------|
| 1 | Vcc | 9600bps |
| 2 | SIN | 19200bps |
| 3 | GND | 38400bps* |
| 4 | SBUSY | 115200bps |
| 5 | NC | (*:Default setting) |
| 6 | /RESET | |

Functions

| Parameter | |
|-----------------------------|--|
| Control command | |
| Scroll display action | |
| Proportional Font function | |
| User-Windows function | |
| AND/OR/XOR Mixture display | |
| Reverse display | |
| Bit image display | |
| Character download function | |
| etc. | |



Leaflet contents, and specifications and external appearance of products, may change without notice.

Please confirm product details in the specification.

(C)Copyright NORITAKE ITRON CORP.