

- A. Fixed black ABS cap with slotted opening to allow size adjustment.
- B. 300 Series Stainless Steel Backplate forms channel to hold up to 10 links of band allowing size adjustment.
- C. 4mm snap stud machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force. Durable, providing long life well beyond that of sheet metal snaps.
- D. Premium metal expansion wrist strap. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.630".

1	ltem	Description	Circumferen		
L			Minimum	Maximum	Width
	<u>09200</u>	Band only, red and blue	5.75 in.	13 in.	0.630"
	<u>09041</u>	Band only, black	5.75 in	13 in.	0.630"
	09042	Band only, X-large, black	6.25 in.	14.5 in.	0.630"
ſ	<u>09085</u>	Band black with 6 ft. coil cord	5.75 in.	13 in.	0.630"
	<u>91070</u>	Band black, 6ft. cord & angle banana, black	5.75 in.	13 in.	0.630"

- E. .002" polyphenylsulfone sheet is laminated to each link. Provides >5,000 volt RMS insulation per ASTM D149. Scratch resistant.
- F. Size is adjusted by sliding 1 to 10 links of the band into the backplate "C" channel.
- G. 300 Series Stainless Steel clip for electrical contact between snap stud and backplate.
- H. Underwriters Laboratory listing 90P1C.

Meets or exceeds requirements of EOS/ESD-S1-1987.

Made in America

## **Premium Metal Expansion Wrist Straps**

**DESCO WEST:** 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178 FAX (909) 627-7449

**DESCO EAST:** ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

02021-1407 **DRAWING NUMBER** 09041

DATE: April 2011