



## FEATURES

- Identifies packages that should be opened only in ESD protected areas
- For use in shipping of ESD sensitive items
- Includes ESD Susceptibility symbol
- Heavy-duty, reinforced shipping tape
- Packaged 10 rolls per case
- Made in America

## SPECIFICATIONS:

- 3" x 450' Non-Asphaltic Re-Enforced Tape
- Core Size: No Core
- Paper: 25# Top Sheet and 25# Bottom Sheet
- Temp. Range: 32°F to 100°F
- Package Quantity: 10 Rolls
- Thickness: 5.8 mil
- Adhesive: Water-activated modified starch
- Tensile Strength: Machine Direction @ 55lbs and Cross Direction @ 25lbs
- Recommended for Carton Weight: up to 45 lbs



Made in America

ITEM	DESCRIPTION
47100	CARTON SEALING TAPE, 10/CASE

Use sealing tape with the ESD susceptibility symbol to identify packages that should be opened only in ESD protected areas. "The ESD susceptibility symbol incorporates a reaching hand in a triangle with a slash through it and is used to indicate that an electrical or electronic device or assembly is susceptible to damage from an ESD event." (ANSI-ESD S8.1 Symbols)

## CARTON SEALING TAPE

# PROTEKTIVE PAK

PROTEKTIVE PAK  
13520 MONTE VISTA AVENUE, CHINO, CA 91710  
PHONE (909) 627-2578, FAX (909) 363-7331  
www.protektivepak.com

**DRAWING NUMBER**  
47100

**DATE:**  
11/05