



SPECIFICATIONS

- Dissipative Vinyl Badge Holder
 - Material Thickness: 0.012" (1S) front, & .024" (1S) back
 - Material Tolerance (thickness): $\pm 10\%$
 - Material Color: matte front & back
- Highly visible yellow header
- Includes a 1/8" x 9/16" punch through slot, setback 3/8" from top
- 4 3/8" x 2 11/16" (Outer Dimension)
- Opening setback 3/4" from top with zipper closure
- ESD protection symbol in bottom left corner of the badge holder
- Embossing with: Menda and Made In America along the bottom of the badge holder on the back
- Rtt: 10E6 - 10E10 ohms per ANSI/ESD S11.11
- Low Charging: < 100 volts
- Genuine Made In America - accept no substitutes
- We can do customs just let us know your insert size

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20-2008 section 2.4 Sources of Static Electricity]

Specifications and procedures subject to change without notice.



VERTICAL ESD CARD HOLDER, 2 1/8" x 3 3/8" INSERT SIZE, W/ YELLOW HEADER & ZIPPER CLOSURE

3651 WALNUT AVENUE, CHINO, CA 91710
 PHONE: (909) 627-2453 FAX: (951) 755-8848
 WEBSITE: Menda-ID.com

DRAWING NUMBER
35016

DATE:
January 2011

+/- 1/16" tolerances on dimensions unless specified

