

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
4/04/08	A	ADDED "ROHS COMPLIANT" UPDATED MATERIAL NOTES	T.B.	B.S.	
03/22/13	B	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	


NOTES:

1. MATERIAL:

- HOUSING : BLACK POLYPROPYLENE
FLAMMABILITY RATING- UL94-HB, UL FILE NO. E216959
- RIVETS: BRASS, NICKLE PLATED.
- SPRING: 302 STAINLESS STEEL, NICKLE PLATED.
- TEMPERATURE RANGE: -10°C TO +110°C
- 9 VOLTS SNAPS: BRASS, NICKLE PLATED.
- CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER EIA-540J000
- ROHS 2 COMPLIANT

MOUNTING INSTRUCTION:

USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT. ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By B.S.
			Approved By T.B.
decimal ±.5 (.020)	Title FOUR "AAA" CELL HOLDER		
Fractional ± .8 (.030)		Date 03/22/13	Drawing Number BC4AAASF
Angular ± 3°			