





Date	SYM	REVISION RECORD	AUTH	DR.	CK.
11/19/05	A	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
3/04/06	B	UPDATED MATERIAL SPEC.	T.B.	B.S.	
3/18/06	C	UPDATED DIMENSIONS	T.B.	B.S.	
4/29/06	D	ADDED CONTACT RESI. INFO	T.B.	B.S.	
10/02/09	E	REDRAWN. DIM. 59.70 WAS 56.30 DIM. 13.70 WAS 13.00 DIM. 16.00 WAS 16.40	T.B.	B.S.	



NOTES:

- Plastic material - Polypropylene, Black
- Flammability Rating -UL94-HB, UL File NO. E216959
- Temperature Range: -10°C to +100°C
- Springs - Nickel Plated Spring Steel
- Rivets - Brass, Nickel Plated
- Lugs - Brass, Nickel Plated
- Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000
- ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)		Scale	Drawn By B.S.
Fractional ± .8 (.030)	Title ONE "AA" CELL HOLDER		
Angular ± 3°	Date 10/02/09	Drawing Number BCAAL	
		Approved By T.B.	