



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
11/12/05	A	ADDED "ROHS COMPLIANT"	T.B.		B.S.
3/18/06	B	UPDATED MATERIAL SPEC.	T.B.		B.S.
5/06/06	C	ADDED CONTACT RESI. INFO.	T.B.		B.S.

ORDERING CODE BH2C

L-Solder Lugs
W-(6") Wire Leads
SF-9Volt type snaps
B- Bump plates



Solder Lugs shown




0.624 [15.85]

SPECIFICATIONS

Plastic material - Polypropylene
Flammability Rating -UL94-HB, UL File NO. E216959
Temperature Range: -10°C to +100°C
Springs - Nickel Plated Spring Steel
Wire - 26 AWG, UL1007, CSA
Rivets - Brass, Nickel Plated
9Volt Snaps - Brass, Nickel Plated
CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER
EIA-540J000

ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By T.S.
decimal ±.5 (.020)		1=1	Approved By T.B.
Fractional ± .8 (.030)	Title TWO "C" CELL HOLDER		
Angular ± 3°	Date 5/06/06	Drawing Number BH2CL	