


DATE	SYM	REVISION RECORD	AUTH	DR.	CK.
2/03/07	A	ADDED "ROHS COMPLIANT"	T.B.	B.S.	




ORDERING CODE **BH44AA**

SOLDER LUGS = L
 (6") WIRE LEADS = W
 9 VOLT TYPE SNAPS = SF

Note: Dimensions in mm. (inches)

SPECIFICATIONS :

Plastic material - Polypropylene, Black
 Flammability rating-UL94 HB, UL file no. E216959
 Temperature Range: -10°C to +100 °C
 Springs - nickel plated spring steel
 Rivets - Brass, nickel plated
 9 Volts Snaps - Brass, nickel plated
 Contact resistance: Under 50m Ω for +/- contacts per EIA-540J000
 ROHS COMPLIANT

TOLERANCES (EXCEPT AS NOTED)		 Memory Protection Devices, Inc. 200 Broad Hollow Road, Farmingdale, New York 11735	
DECIMAL			
+ .5 (.020")		NONE	B.S.
- .5 (.020")			APPROVED BY
FRACTIONAL	TITLE		
+ .8 (.030")	FOUR "AA" CELL HOLDER		
- .8 (.030")			
ANGULAR	DATE	DRAWING NUMBER	
+ 3°	2/03/2007	BH44AAW	
- 3°			