

I	Date	SYM	REVISION RECORD	AUTH	DR.	CK.
Ī						
Ī						
Ī						
ĺ						

4	<b>(5</b> )
	_3.02 [0.119]

N0.	PART NAME	MATERIAL	QTY.	Tolerance		Mem	ory Protection Devices, Inc			
1	COVER	PVC COVER OVER FIBERBOARD	1	(Except as noted)		200	Broad Hollow Road, Farmingdale, New York 11735			
2	BLACK WIRE(-)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C		decimal	imal		Scale	Drawn By B.S.		
3	RED WIRE (+)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	±.5 (.020)					Approved By T.B.	
4	FEMALE SNAP	BRASS NICKLE PLATED	1	`					Approved by 1.D.	
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title	O MOLE DARREDM CNAD E CENTE 4" NUDE LEADO				
				± .8 (.030)		9 VOL	I BATTERY SI	RY SNAP-T STYLE-4" WIRE LEADS		
				Angular	Date		Drawing Number			
				± 3°	05/25	5/01	BS4T			