



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
9/18/07	B	ADDED SECOND NOTCH	T.B.	B.S.	
10/12/07	C	UPDATED DIM. FOR PCB LAYOUT	T.B.	B.S.	
6/06/08	D	Temperature range was -40°C to +315°C	T.B.	B.S.	
2/26/10	E	Dim. 29.30 was 31.80	T.B.	B.S.	
3/05/10	F	Updated PCB Layout	T.B.	B.S.	



SPECIFICATIONS:

- * Holder material- 30% glass reinforced Liquid Crystal Polymer resin, UL File No. E123598, UL94V-0
- * Color: White
- * Contacts : 0.020" thick PHOS-BRONZE, GOLD FLASH
- * Temperature range: -40°C to +280°C
- * Vibration Test: 10-50-10 Hz swept in 60 seconds
X,Y,Z direction: 1 hour each direction
- * Result: No dislodgement of the cell or damage
No discontinuity over 10 micro-seconds
- * Shock Test: Half sine wave acceleration 150G. 6 micro-seconds
3 shock pulses each direction per axis, total of 18 pulses
- * Result: No evidence of physical damage
- * ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
±.5 (.020)			Approved By T.B.
Fractional	Title		
± .8 (.030)	SURFACE MOUNT BATTERY HOLDER FOR CR2032		
Angular	Date	Drawing Number	
± 3°	3/05/10	BU2032SM-JJ-GTR	