


Wireless LAN OEM Serial Port Adapter



Product Brief OWS451 (UART interface)

The OEM WIRELESS LAN SERIAL PORT ADAPTER™ 451 series from connectBlue is a module with UART interface and fully embedded TCP/IP stack and driver. It is developed for reliable, high demanding industrial devices and applications providing state of the art low power features and dual-band support for both 2.4GHz and 5GHz radio bands. The module is presented as a serial port/UART to the host. Raw serial data is sent to the module, which will package the data into TCP/UDP packages and transmit via Wireless LAN. The module minimizes the work needed to implement Wireless LAN (IEEE 802.11a/b/g/n) in a device as it provides all hardware, type approval, EMC certification etc.

KEY FEATURES

- Supports 802.11a/b/g/n
- Dual-band radio, 2.4GHz and 5GHz
- 802.11n space time block code for extended range and throughput
- High Speed UART interface up to 1.8Mbps
- Radio type approved for Europe, US and Canada (R&TTE, FCC, IC)*
- Compliant with EMC standards*
- Industrial temperature range -40 to +85°C*
- Low power consumption
- Security support: Enterprise, WPA2-PSK, WPA-PSK, PEAP, LEAP, WEP64/128
- Quality of Service: 802.11e and WMM*
- Ad-hoc and infrastructure mode
- Extended Data Mode™ for individual control of up to 7 channels*
- Internal or dual external antennas

IEEE 802.11 SPECIFICATIONS

Conforms to 802.11a/b/g/e/i/h/j, drafts 802.11k/r/s, single-stream 802.11n standards and WMM

PHY/MAC

802.11a/b/g/n (single stream n)
Dual-band radio, 2.4GHz and 5GHz
Max output power: +17dBm
Integrated baseband and MAC processing
Advanced power management
802.11n space time block code support
Regulatory domain support
Antenna receive diversity

SOFTWARE

All software embedded in the module (TCP/IP stack and serial port adapter application)
Configurable via AT commands (via Wireless LAN or serial port)
Extended Data Mode™ for individually controlled multipoint data channels* (different data can be sent to / received from each slave)

OPERATIONAL MODES

BSS (infrastructure) and IBSS (ad-hoc)

SECURITY

Enterprise modes
WPA-PSK, WPA2-PSK
PEAP, LEAP
802.11i
WEP64/128
TKIP, AES (CCMP)

QUALITY OF SERVICE*

802.11e
WMM

ADDITIONAL FEATURES

TCP/UDP protocol support
TX Power calibration
Link adaptation
Fragmentation
DTIM based power management
DHCP server and client
DNS-resolver
Fast roaming
LLDP

HOST INTERFACE

UART Logic Level
Supported baud rates: 1200 bps - 1.8 Mbps
Support for non-standard baud rates
Flow control: CTS/RTS or none
Full modem signalling

CONNECTORS

Board-to-board connector
Solder pads
6-pin JST connector (optional)

* In progress

ANTENNAS

Single internal or dual external (receive diversity)

POWER

3.3-5.5 VDC
Deep sleep mode (average): TBA
Sleep mode, connected (average): TBA
Active mode, transmitting at 115 kbps (average): TBA

DIMENSIONS / WEIGHT

Dimensions: 23 x 36 x 3.2 mm
Weight: 3.7g

TYPE APPROVAL*

R&TTE (Europe)
FCC/CFR 47 part 15 unlicensed modular transmitter approval
IC (Industrie Canada)

ENVIRONMENTAL*

Operating temperature: -40 to +85 °C
Storage temperature: -40 to +85°C
Humidity RH 5-90% non-condensing

CERTIFICATIONS AND COMPLIANCE*

R&TTE Directive 1999/5/EC:

Effective use of frequency spectrum
EN 300 328 V1.7.1 (2006-10)

EMC Directive: 89/336/EEC
EN 301 489-1 V1.8.1 (2008-04)
EN 301 489-17 V1.3.2 (2007-06)
EN 61000-6-2 (2005)

Safety Compliance
EN 50371:2002
EN 60950-1:2006 and/or IEC 60950-1:2006

Medical Electrical Equipment
IEC 60601-1-2 (2007) (for single antenna configurations)

ARTICLE NUMBERS

cB-OWS451i-04
OEM Wireless LAN SPA 451 with integrated antenna, board-to-board connector and solder pads.

cB-OWS451i-06
OEM Wireless LAN SPA 451 with integrated antenna, board-to-board connector, solder pads and JST connector.

cB-OWS451x-04
OEM Wireless LAN SPA 451 with connector for external antenna, board-to-board connector and solder pads.

cB-OWS451x-06
OEM Wireless LAN SPA 451 with connector for external antenna, board-to-board connector, solder pads and JST connector.

connectBlue™

The strongest connection in a wireless world

HEAD OFFICE: connectBlue AB | Norra Vallgatan 64 3V | SE-211 22 Malmö | Sweden | Phone +46 40-6307100 | Fax +46 40-237137
US OFFICE: connectBlue Inc. | 1460 N. Sandburg Terrace, Suite 2412 | Chicago, IL 60610 | USA | Phone +1 312 927 5859 | Fax +1 312 277 3209
GERMAN OFFICE: connectBlue GmbH | Raiffeisenstrasse 19 | DE-85276 Pfaffenhofen | Germany | Phone +49 8441 786 4160 | Fax +49 8441 786 4161
info@connectblue.com | us-info@connectblue.com | www.connectblue.com

Printed in Sweden. ©2010 connectBlue AB. All rights reserved. All specifications are subject to change without notice. The connectBlue word mark and logo are owned by connectBlue AB. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by connectBlue is under license.