



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)821-7413  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 7005**  
**80 - 6000 MHz THREE CHANNEL**  
**50 to 280 WATTS**  
**HIGH POWER RF AMPLIFIER**

**Solid State  
 Broadband High  
 Power RF Amplifier**

The 7005 is a three channel amplifier that covers the 80 – 6000 MHz frequency range. Each channel can transmit independently and includes its AC, RF and IEEE-488 GPIB interface .

The 7005 is based on OphirRF standard legacy proven systems 5072FE-001, 5153FE with coupling port, and 5193FE-001.

**CIRCUIT PROTECTIONS**

- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage
- ◇ VSWR

**INDICATIONS**

- ◇ Thermal Fault
- ◇ Forward Detected Power
- ◇ Reverse Detected Power
- ◇ Forward Sampling Port

**CONTROLS**

- ◇ Standby Mode
- ◇ Gain Adjustment (VVA)
- ◇ Automatic level Control



Specifications subject to change without notice

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	Channel 1 80 to 1000MHz Channel 2 100 to 2500MHz Channel 3 2500 to 6000MHz
2	Saturated Output Power	Channel 1 280W typical Channel 2 80W typical Channel 3 50W typical
3	Power Output @ 1dB Comp.	Channel 1 150W typical Channel 2 60W typical Channel 3 30W typical
4	Nominal input power drive for rated output power	0dBm
5	Gain Flatness	+/- 2.5 dB max with no ALC +/- 1.0 dB max with Internal Leveling
6	IP <sub>3</sub>	Typical +8dB above P1dB
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical
9	Spurious Signals	> -60 dBc typical
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	Ch 1 208-240VAC, 1Ø single Phase Ch 2 & 3 100-240VAC, 1Ø single Phase
12	AC Input Power	Channel 1 4000W max Channel 2 1200W max Channel 3 800W max
13	RF Coupling port for each Channel	Channel 1 53dB below peak power Channel 2,3 43dB below peak power
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<b>Mechanical</b>		
16	Dimensions	42" x 24" x 30" (H x W x D) max
17	Weight	350 lb. max
18	Connectors	Type-N
19	User Interface	IEEE-488 GPIB
20	Front panel interface	Display, RF Input/Output Connectors AC Input/Output Switch, Coupling port
21	Rear panel interface	AC Connectors, IEEE-488 Connector
22	Grounding	Chassis
23	Cooling	Internal Forced Air
<b>Environmental</b>		
24	Operating Temperature	0° C to +50° C
25	Operating Humidity	95% Non-condensing
26	Operating Altitude	Up to 10,000' Above Sea Level
27	Shock and Vibration	Normal Truck Transport