


## Bulk Metal® Foil Technology Precision Foil Power Surface Mount Resistors in TO-220 Configuration with TCR of $\pm 2$ ppm/°C, Tolerance of to $\pm 0.01$ % and Power Rating to 8 W



Any value at any tolerance within resistance range

Models VPR220S AND VPR221S, made from Vishay Bulk Metal® foil, offer low TCR, high stability, tight tolerance and fast response time in a small, molded resistor. Model VPR220S is a 2 lead device. Model VPR221S is a 4 lead Kelvin connected device. The 4 leaded version is highly recommended for precision applications requiring ohmic values of 100R or less.

TABLE 1 - VPR220S			
RESISTANCE RANGE ( $\Omega$ ) <sup>1</sup>	TIGHTEST TOLERANCE	TYPICAL TCR <sup>2</sup>	MAXIMUM TCR <sup>2</sup>
50 to 10K	$\pm 0.01$ %	$\pm 2$	$\pm 5$ ppm/°C
25 to < 50	$\pm 0.02$ %	$\pm 2$	$\pm 7$ ppm/°C
10 to < 25	$\pm 0.05$ %	$\pm 2$	$\pm 10$ ppm/°C
5 to < 10	$\pm 0.1$ %	$\pm 2$	$\pm 13$ ppm/°C

weight = 1 g maximum

### Notes

- Lower or high values available upon request
- 55 °C to + 125 °C, + 25 °C ref.

TABLE 2 - VPR221S			
RESISTANCE RANGE ( $\Omega$ ) <sup>1</sup>	TIGHTEST TOLERANCE	TYPICAL TCR <sup>2</sup>	MAXIMUM TCR <sup>2</sup>
10 to < 500	$\pm 0.01$ %	$\pm 2$	$\pm 5$ ppm/°C
1 to < 10	$\pm 0.02$ %	$\pm 2$	$\pm 5$ ppm/°C
0.5 to < 1	$\pm 0.05$ %	$\pm 2$	$\pm 5$ ppm/°C

weight = 1.2 g maximum

### Notes

- Lower or high values available upon request
- 55 °C to + 125 °C, + 25 °C ref.

\* Pb containing terminations are not RoHS compliant, exemptions may apply

### FEATURES

- Temperature coefficient of resistance (TCR):  $\pm 2$  ppm/°C typical (- 55 °C to + 125 °C, + 25 °C Ref.)
- Tolerance: to  $\pm 0.01$  % (see tables 1 and 2)
- Electrostatic discharge (ESD): above 25 000 V
- Load life stability:  $\pm 0.005$  % (25 °C, 2000 h at rated power)
- Resistance range: 0.5  $\Omega$  to 10 k $\Omega$
- Power rating: 8 W chassis mounted (per MIL-PRF-39009)
- Non inductive, non capacitive design
- Rise time: 1 ns without ringing
- Current noise: < - 40 dB
- Voltage coefficient: < 0.1 ppm/V
- Non inductive: < 0.08  $\mu$ H
- Non hot spot design
- Thermal EMF: 0.05  $\mu$ V/°C typical
- Terminal finishes available: lead (Pb)-free tin/lead alloy
- Any value available within resistance range (e.g. 1K234)
- Prototype samples available from 48 h. For more information, please contact [foil@vishaypg.com](mailto:foil@vishaypg.com)
- For better performances, please see VPR220SZ and VPR221SZ datasheets



RoHS\*  
COMPLIANT







FIGURE 1 - POWER DERATING CURVE



**FIGURE 2 - TYPICAL TCR CURVE**



**FIGURE 3 - TRIMMING TO VALUES**  
(Conceptual Illustration)



**TABLE 3 - SPECIFICATIONS**

<b>Load Life Stability at 2000 h</b>	± 0.05 % max. ΔR under full rated power at + 25 °C
<b>Power Rating at + 25 °C</b>	8 W or 3 A <sup>1)</sup> on heat sink <sup>2)</sup>
	1.5 W or 3 A <sup>1)</sup> in free air
	Further derating not necessary
<b>Current Noise</b>	< 0.010 μV (rms)/V of applied voltage (- 40 dB)
<b>High Frequency Operation</b>	
Rise time	1 ns without ringing
Inductance <sup>3)</sup> (L)	0.1 μH maximum: 0.03 μH typical
Capacitance (C)	1.0 pF maximum: 0.5 pF typical
<b>Voltage Coefficient<sup>4)</sup></b>	< 0.1 ppm/V
<b>Operating Temperature Range</b>	- 55 °C to + 150 °C
<b>Maximum Working Voltage</b>	300 V. Not to exceed power rating
<b>Thermal EMF<sup>5)</sup></b>	0.15 μV/°C maximum (lead effect)


**Notes**

1. Whichever is lower
2. Heat sink chassis dimensions and requirements per MIL-R-39009/1B:


DIMENSION	INCHES	mm
L	6.00	152.4
W	4.00	101.6
H	2.00	50.8
T	0.04	1.0

3. Inductance (L) due mainly to the leads
4. The resolution limit of existing test equipment (within the measurement capability of the equipment, or “essentially zero”)
5. μV/°C relates to EMF due to lead temperature difference


**FIGURE 4 - VPR220S AND VPR221S FORMING DIMENSIONS** in inches (millimeters)




**FIGURE 5 - VPR220S DIMENSIONS** in inches (millimeters)




**FIGURE 7 - VPR221S DIMENSIONS** in inches (millimeters)



**FIGURE 6 - VPR220S LAND PATTERN DIMENSIONS** in inches (millimeters)




**FIGURE 8 - VPR221S LAND PATTERN DIMENSIONS** in inches (millimeters)



**TABLE 4 - GLOBAL PART NUMBER INFORMATION**


NEW GLOBAL PART NUMBER: Y11235R00000Q9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y1123 5R00000 Q 9 L:

TYPE: VPR221S  
 VALUE: 5.0 Ω  
 ABSOLUTE TOLERANCE: ± 0.02 %  
 TERMINATION: lead (Pb)-free  
 PACKAGING: bulk pack

HISTORICAL PART NUMBER: VPR221ST 5R0000 Q B (will continue to be used)



**Note**

\* Application engineering release: for non-standard requests, please contact application engineering

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.