

## Ultra High Precision Z-Foil Power Resistor in TO-220 Configuration with TCR of $\pm 0.05$ ppm/ $^{\circ}$ C, Tolerance to $\pm 0.01$ % and Power Rating to 8 W



Vishay Foil Resistors manufacture any resistance value within the given resistance range (e.g. 10  $\Omega$  or 10.1234  $\Omega$ ) without influencing cost or lead time

Model VPR220Z, made from Vishay Bulk Metal<sup>®</sup> Z-foil, offers very low TCR, high stability, tight tolerance, low PCR and fast response time in a small molded resistor.

The Z-foil technology provides a significant reduction of the resistive components sensitivity to ambient temperature variations and applied power changes. Designers now can guarantee a high degree of stability and accuracy in fixed resistor applications using solutions based on Vishay's revolutionary Z-foil technology.

Our application engineering department is available to advise and make recommendations. For non-standard technical requirements and special applications, please contact us.

### FEATURES

- Temperature coefficient of resistance (TCR):  $\pm 0.05$  ppm/ $^{\circ}$ C typical (0  $^{\circ}$ C to + 60  $^{\circ}$ C)  
 $\pm 0.2$  ppm/ $^{\circ}$ C typical (- 55  $^{\circ}$ C to + 125  $^{\circ}$ C, + 25  $^{\circ}$ C ref.)
- Tolerance: to  $\pm 0.01$  %
- Power coefficient of resistance (PCR) "ΔR due to self heating": 4 ppm/W typical
- Electrostatic discharge (ESD) above 25 000 V
- Load life stability:  $\pm 0.005$  % (25  $^{\circ}$ C, 2000 h at rated power)
- Resistance range: 5  $\Omega$  to 10 k $\Omega$  (Any value available within resistance range e.g. 1K2345)
- Power rating: 8 W chassis mounted (per MIL-PRF-39009)
- Thermal stabilization < 1 s
- Rise time: 1 ns without ringing
- Optimized for military and space applications according to EEE-INST-002 screening and MIL-PRF 39009
- Non inductive, non capacitive design
- Current noise: < - 40 dB
- Voltage coefficient: < 0.1 ppm/V
- Non inductive: < 0.08  $\mu$ H
- Non hot spot design
- Thermal EMF: 0.05  $\mu$ V/ $^{\circ}$ C typical
- Terminal finishes available: lead (Pb)-free, tin/lead alloy
- Also available in a surface mount version, the VPR220SZ
- Prototype samples available from 72 h. For more information, please contact [foil@vishaypg.com](mailto:foil@vishaypg.com)
- For higher performances please contact us




Available  
RoHS\*  
COMPLIANT

RESISTANCE RANGE ( $\Omega$ )	TIGHTEST RESISTANCE TOLERANCE	TYPICAL TCR AND MAX. SPREAD (ppm/ $^{\circ}$ C)
50 to 10K	$\pm 0.01$ %	$\pm 0.2 \pm 2.3$
25 to < 50	$\pm 0.02$ %	
10 to < 25	$\pm 0.05$ %	
5 to < 10	$\pm 0.1$ %	

Weight = 1 g maximum

FIGURE 1 - POWER DERATING CURVE



\* Pb containing terminations are not RoHS compliant, exemptions may apply


**TABLE 2 - SPECIFICATIONS**

<b>Load Life Stability at 2000 h</b>	± 0.05 % max. ΔR under full rated power at + 25 °C
<b>Power Rating at + 25 °C</b>	8 W or 3 A <sup>1)</sup> on heat sink <sup>2)</sup> 1.5 W or 3 A <sup>1)</sup> in free air <b>Further derating not necessary.</b>
<b>Current Noise</b>	< 0.010 μV (rms)/V of applied voltage (- 40 dB)
<b>High Frequency Operation</b> Rise time Inductance <sup>3)</sup> (L) Capacitance (C)	1 ns 0.1 μH maximum: 0.03 μH typical 1.0 pF maximum: 0.5 pF typical
<b>Voltage Coefficient<sup>4)</sup></b>	< 0.1 ppm/V
<b>Operating Temperature Range</b>	- 55 °C to + 150 °C
<b>Maximum Working Voltage</b>	300 V. Not to exceed power rating.
<b>Thermal EMF<sup>5)</sup></b>	0.15 μV/°C maximum (lead effect)


**Notes**

1. Whichever is lower.
  2. Heat sink chassis dimensions and requirements per MIL-PRF-39009:
- | DIMENSION | INCHES | mm    |
|-----------|--------|-------|
| L         | 6.00   | 152.4 |
| W         | 4.00   | 101.6 |
| H         | 2.00   | 50.8  |
| T         | 0.04   | 1.0   |
3. Inductance (L) due mainly to the leads.
  4. The resolution limit of existing test equipment (within the measurement capability of the equipment, or “essentially zero”).
  5. μV/°C relates to EMF due to lead temperature difference.


**FIGURE 2 - TRIMMING TO VALUES**  
(conceptual illustration)




**FIGURE 3 - TYPICAL TCR CURVE Z-FOIL**




**FIGURE 4 - VPR220Z TESTS:**  
**5R, 10 UNITS**



**FIGURE 5 - VPR220Z LOAD LIFE, 10 kΩ**  
**P<sub>NOM.</sub>, 25 °C, 20 UNITS**




**FIGURE 6 - VPR220Z FORMING DIMENSIONS** in inches (millimeters)



**TABLE 3 - GLOBAL PART NUMBER INFORMATION**


NEW GLOBAL PART NUMBER: Y1622350R650Q9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y1622 350R650 Q 9 L:

TYPE: VPR220Z  
 VALUE: 350.65 Ω  
 ABSOLUTE TOLERANCE: ± 0.02 %  
 TERMINATION: lead (Pb)-free  
 PACKAGING: bulk pack

HISTORICAL PART NUMBER: VPR220ZT 350R65 Q B (will continue to be used)



**Note**

\* For non-standard requests, please contact application engineering.

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.