



| Magnetic properties | Conditions | Min | Typ | Max | Unit |
|---------------------|------------|--------|-----|-----|------|
| Pull-In | at 20°C | 50 | | 135 | |
| Test equipment | | KMS-11 | | | |

| Contact data 66/3 | Conditions | Min | Typ | Max | Unit |
|-----------------------------|---|------|-----|-----|------|
| Contact-No. | | 66/3 | | | |
| Contact-form | | A | | | |
| Contact rating | Any DC combination of V & A not to exceed their individual max.'s | | | 10 | W |
| Switching voltage | DC or Peak AC | | | 200 | V |
| Carry current | DC or Peak AC | | | 1 | A |
| Switching current | DC or Peak AC | | | 0,5 | A |
| Contact resistance static | Measured with 40% overdrive Start Value | | | 100 | mOhm |
| Breakdown voltage (> 20 AT) | according to IEC 255-5 | 400 | | | VDC |

| Special Product Data | Conditions | Min | Typ | Max | Unit |
|----------------------|------------|-------------|-----|-----|------|
| Housing material | | epoxy resin | | | |

| Environmental data | Conditions | Min | Typ | Max | Unit |
|-----------------------|-----------------------------|--------------|-----|-----|------|
| Shock | 1/2 sine wave duration 11ms | | | 30 | g |
| Vibration | from 10 - 2000 Hz | | | 20 | g |
| Operating temperature | | -20 | | 130 | °C |
| Storage temperature | | -35 | | 130 | °C |
| Washability | | fully sealed | | | |