

Features

- ◆ Ultra wide 4 : 1 input range
- ◆ Input filter to meet EN 55022, Class A and FCC, level A without external components
- ◆ Extended operating temperature range -40°C to 85°C
- ◆ I/O isolation 1'500 VDC
- ◆ DIP-24 package
- ◆ High reliability, MTBF >1.0 Mio. h
- ◆ 3-year product warranty



The TEN 3WIN Series is a drop in replacement of the prevalent TEN 3WI Series. The up-to date design enables a cost reduction without any compromise to reliability and function. They come with an internal filter to meet EN55022 class A without external components. Increased EMC immunity and extended operating temperature range of -40°C to 85°C make these converters an ideal solution for cost critical but demanding applications. With the standard pinning it is a drop in replacement for common 3 Watt converters in DIP24 package.

Models

Ordercode	Input voltage range	Output voltage	Output current max.	Efficiency max.
TEN 3-2410WIN	9.0 – 36 VDC (nominal 24 VDC)	3.3 VDC	750 mA	77 %
TEN 3-2411WIN		5.0 VDC	600 mA	79 %
TEN 3-2412WIN		12 VDC	250 mA	82 %
TEN 3-2413WIN		15 VDC	200 mA	83 %
TEN 3-2415WIN		24 VDC	125 mA	81 %
TEN 3-2421WIN		± 5.0 VDC	± 250 mA	80 %
TEN 3-2422WIN		± 12 VDC	± 125 mA	82 %
TEN 3-2423WIN		± 15 VDC	± 100 mA	82 %
TEN 3-4810WIN	18 – 75 VDC (nominal 48 VDC)	3.3 VDC	750 mA	77 %
TEN 3-4811WIN		5 VDC	600 mA	80 %
TEN 3-4812WIN		12 VDC	250 mA	83 %
TEN 3-4813WIN		15 VDC	200 mA	84 %
TEN 3-4815WIN		24 VDC	125 mA	82 %
TEN 3-4821WIN		± 5.0 VDC	± 250 mA	80 %
TEN 3-4822WIN		± 12 VDC	± 125 mA	82 %
TEN 3-4823WIN		± 15 VDC	± 100 mA	82 %

Input Specifications

Input current no load	24 Vin models 48 Vin models	30 mA typ. 20 mA typ.
Start-up voltage	24 Vin models: 48 Vin models:	9.0 VDC (or lower) 18 VDC (or lower)
Under voltage shut down (lock-out circuit)	24 Vin models: 48 Vin models:	8.5 VDC max. 17.5 VDC max.
Surge voltage (1 sec. max.)	24 Vin models 48 Vin models	50 V max. 100 V max.
Reflected ripple current	24 Vin models 48 Vin models	15 mA typ 10 mA typ.
Conducted noise		EN 55022 class A without external components
ESD (electrostatic discharge)		EN 61000-4-2, air ± 8 kV, contact ± 6 kV, perf. criteria A
Radiated immunity		EN 61000-4-3, 10 V/m, perf. criteria A
Fast transient / surge (with external input capacitor) – external input capacitor		EN 61000-4-4, ± 2 kV, perf. criteria A EN 61000-4-5, ± 1 kV perf. criteria A Nippon chemi-con KY 200 μ F, 100 V, ESR 48 mOhm
Conducted immunity		EN 61000-4-6, 10 Vrms, perf. criteria A
Short circuit input power		2000 mW max.
Internal power dissipation		1200 mW max.

Output Specifications

Voltage set accuracy		± 2 % max.
Regulation	– Input variation Vin min. to Vin max. – Load variation 0 – 100 %	1.0 % max.
	single output models dual output models balanced load	1.0 % max. 2.0 % max.
Minimum load		not required
Ripple and noise (20 MHz bandwidth)		70 mVpk-pk max
Transient response time (25% load step change)		500 μ s max.
Transient response deviation (25% load step change)		± 5 % max.
Temperature coefficient		± 0.02 %/K
Current limitation		>120 % of Iout max., constant current
Short circuit protection		continuous

Output Specifications (continued)

Capacitive load	3.3 VDC models:	680 μ F max.
	5.0 VDC models:	470 μ F max.
	12 VDC models:	330 μ F max.
	15 VDC models:	220 μ F max.
	24 VDC models:	100 μ F max.
	\pm 5.0 VDC models:	220 μ F max. (each output)
	\pm 12 VDC models:	150 μ F max. (each output)
	\pm 15 VDC models:	100 μ F max. (each output)

General Specifications

Temperature ranges	- Operating (natural convection cooling 20 LFM)	-40°C to +85°C
	- Case temperature	+100°C max.
	- Storage	-55°C to +125°C
Derating		3.3 %/K above 70°C
Humidity (non condensing)		95 % rel H max.
Reliability, calculated MTBF (MIL-HDBK-217 F, at +25°C, ground benign)		>1 Mio. h
Isolation voltage (60 sec.)	- Input/Output	1'500 VDC
Isolation capacitance	- Input/Output	300 pF max.
Isolation resistance	- Input/Output (500 VDC)	>1'000 M Ohm
Switching frequency		90 kHz min. (pulse frequency modulation PFM)
Safety standards		cUL/UL 60950-1, IEC/EN 60950-1
Safety approval		CSA file no. 226037 http://directories.csa-international.org
Environmental compliance	- Reach	www.tracopower.com/products/reach-declaration.pdf
	- RoHS	RoHS directive 2011/65/EU


Application note: www.tracopower.com/products/ten3win-application.pdf

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Physical Specifications

Casing material	non conductive FR4
Potting material	epoxy (UL 94V-0 rated)
Pin material	copper alloy with gold plated subplate
Weight	12.8 g (0.45 oz)
Soldering temperature	max. 260°C / 10 sec.

Outline Dimensions



Dimensions in [mm], () = Inch
 Pin diameter $\varnothing 0.5 \pm 0.05$ (0.02 \pm 0.002)
 Tolerances ± 0.5 (± 0.02)
 Pin pitch tolerances ± 0.25 (± 0.01)

Pin-Out		
Pin	Single	Dual
2	-Vin (GND)	-Vin (GND)
3	-Vin (GND)	-Vin (GND)
9	No pin	Common
11	ntc	-Vout
14	+Vout	+Vout
16	-Vout	Common
22	+Vin (Vcc)	+Vin (Vcc)
23	+Vin (Vcc)	+Vin (Vcc)

ntc = not to connect