



PocketTach® Mini Tachometers

Choice of Contact or Non-contact Tachometer

For rpm and surface speed measurements

Features:

- · Large easy to read (99,999 count) LCD display
- Autoranging with 0.1% basic accuracy
- · Hold button freezes displayed reading
- Ergonomically designed and pocket sized housing with protective finger guard
- Easy to operate by simply contacting the rotating object with the sensor tip and read
- 461750 Contact model with surface wheels enable tachometer to measure linear surface speeds in ft/min, m/min, and yd/min
- 461700 Non-contact integral light beam model with ideal measurement range up to 6" (150mm) distance
- Complete with 9V battery; 461700 includes reflective tape and 461750 includes surface wheels



Ordering Information:

| 461700 | PocketTach® Mini Photo Tachometer |
|-------------|-------------------------------------|
| 461700-NIST | 461700 with NIST certificate |
| 461750 | PocketTach® Mini Contact Tachometer |
| 461750-NIST | 461750 with NIST certificate |



| Specifications | 461700 | 461750 |
|--------------------|-------------------------------|--------------------------------------|
| Display Counts | 99,999 count LCD | 99,999 count LCD |
| Range rpm | 10 to 99,999rpm | 10 to 20,000rpm |
| ft/min | _ | 3 to 6560ft/min |
| m/min | _ | 1 to 1999.9m/min |
| yd/min | _ | 1 to 5,000yd/min |
| Basic accuracy | ±(0.1%rdg +2d) | $\pm (0.1\% \text{rdg} + 2\text{d})$ |
| Sampling Time | 1sec>60rpm, >1sec>10 to 60rpm | |
| Max rpm Resolution | 0.001 | 0.001 |
| ft/min Resolution | _ | 0.0001 |
| Dimensions | 4.88 x 1.97 x 1.3" | 5.87 x 1.97 x 1.3" |
| | (124 x 50 x 33mm) | (149 x 50 x 33mm) |
| Weight | 4oz (114g) | 5oz (142g) |

