

Combination Photo/Contact Tachometers

Combines both contact and non-contact models
Choice of Laser-guided model for greater distance non-contact measurements

Features:

- Unique display where characters reverse direction depending on measurement mode you are in
- Large 0.4" (5 digit) LCD display
- Microprocessor based with quartz crystal oscillator to maintain high accuracy
- Tachometer memory stores last, max and min readings
- Provides wide RPM (photo and contact) and Linear Surface Speed (contact) measurements
- Accurate to 0.05% with max resolution of 0.1rpm in either photo or contact mode
- Complete with tips and wheel for rpm or linear surface speed, four 1.5V AA batteries, reflective tape and carrying case

Additional Features (461995):

- Narrow beam Laser photo tachometer for accurate non-contact RPM measurements
- Measurements from up to 6.5ft from the target for improved safety and accessibility



| Specifications for both models | Photo mode | Contact mode |
|--------------------------------|---|--|
| Range (RPM) 461895 | 5 to 99,999 | 0.5 to 20,000 |
| Range (RPM) 461995 | 10 to 99,999 | 0.5 to 20,000 |
| Accuracy | 0.05% rdg +1 digit | |
| Sampling Time | 1 Sec > 60rpm | |
| Surface Speed | | 0.2 to 6560ft/min 0.05 to 1999.9m/min |
| Resolution | 0.1rpm (< 1,000 rpm) 1rpm (>1000rpm) | |
| Power | 4 AA batteries | |
| Dimensions | 8.5 x 2.6 x 1.5"(215 x 65 x 38 mm) | |
| Weight | 10.6 oz (300 g) | |

Ordering Information:

- 461895Combination Contact/Photo Tachometer
 461895-NIST461895 with NIST certificate
 461995Laser Photo/Contact Tachometer
 461995-NIST461995 with NIST certificate
 461937Spare Reflective Tape (10pk, 23" each roll)
 461990Set of Spare Contact Wheels (2 sets of 3)

