

ExStik[®] Waterproof Refillable pH Meter

Features flat surface electrode, RENEW and CALibration alerts, memory, and bargraph
Indicator tells you it's time to replace your electrode and eliminates guesswork

Features:

- ✓ Refillable pH electrode is easily serviced. Fresh reference solution maintains high accuracy. Eliminates concern with shelf life.
- ✓ Flat Surface Electrode measures pH in liquids, semi-solids, and solids. No more electrode breakage or clogged junctions.
- ✓ CAL alerts tells you it's time to recalibrate. Ensures accuracy.
- ✓ Memory records and recalls 15 sequentially tagged readings. Allows detection of changes over time.
- Analog bargraph displayed on LCD. Shows trends in acidity or alkalinity.
- 1, 2 or 3 point calibration automatically recognizes buffer solutions. Order pH buffers separately.
- Automatic Temperature Compensation
- Simultaneous display of pH and Temperature
- Waterproof to IP57 standard
- Display indicates when the reading is stabilized
- Data Hold, Auto power off and low battery indication
- Waterproof design floats in water and protects the meter in wet environment
- Interchangeable probes available for Chlorine & ORP
- Optional weighted base (EX006) holds plastic cup and ExStik[®] meter
- Complete with refillable flat surface pH electrode, 1.5mL bottle KCl, 2 reference junctions, 2 removal tools, protective sensor cap, sample cup with cap, four 3V CR-2032 button batteries, and 48" (1.2m) neckstrap. **Order pH buffers separately**

Ordering Information:

PH110Waterproof Refillable ExStik[®] pH Meter
 PH115Spare Refillable pH ExStik[®] Electrode Module
 PH113Reference Refill Solution Kit for PH110
 EX006.....Weighted base with 5 solution cups
 PH103Tripack buffers (6ea - 4, 7, 10pH & 2 Rinse solutions)
 PH105Spare pH ExStik[®] Electrode Module
 EX007.....Spare sample solution cups (24pk)
 CA903Carrying case for ExStik[™] kit
 RE305.....Spare Probe, ORP
 CL205.....Spare Probe, Chlorine
 EX010.....Extension Cable, 3ft (1 Meter) with probe weight for ExStik
 EX050Extension Cable, 16ft (5 Meter) with probe weight for ExStik
 PH115Spare Probe, pH, Refillable Reference
 PH4-P.....pH 4 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each)
 PH7-P.....pH 7 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each)
 PH10-P.....pH 10 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each)
 CA895Carrying Case, Small with Belt Loop
 EX800.....ExStik 3-in-1 Kit (Chlorine, pH, Temp)
 EX900.....ExStik 4-in-1 Kit (Chlorine, pH, ORP, Temp)
 D0610ExStik DO/pH/Conductivity Kit



Model PH113 Reference Refill Solution Kit includes:

1.5mL bottle KCl,
2 reference junctions and
2 removal tools.



Specifications	
pH	0.00 to 14.00pH
Temperature	23 to 194°F (-5 to 90°C)
Resolution	0.01pH, 0.1°
Accuracy	±0.01pH, ±1.8°F/±1°C
Power	four LR44 button batteries
Dimensions	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)
Weight	3.8oz (110g)

