

# AAL-Series Inclinometer

Dual axis inclinometer  
Measurement range  
+/-2 up to +/- 30°  
with analog output signal



The **AAL-Series** conductive inclination sensor offers a full calibrated inclination sensor module on a PCB. The sensor provides voltage output depending on the inclination angle and related to the specific axis, as well as a voltage based temperature output signal. An optional integrated e<sup>2</sup>-prom contains data on the characteristic curve resp. calibration data. This allows for a high integration into a specific application with excellent performance regarding accuracy and long-term stability.


## FEATURES

- PCB level
- High accuracy
- Temperature compensated
- High resolution
- Analog output signal
- e<sup>2</sup>-prom on board

## APPLICATIONS

- Building control
- Weighing systems
- Truck chassis levelling
- Mobile and stationary cranes
- Lift platforms
- Road construction machines
- Vehicle applications

## dimensions [mm]



## performance specifications

### PARAMETERS

	Conditions	Min	Type	Max	Unit
Measurement range (1)		-2 (-30)		+2 (+30)	°
Resolution (2)		0.001		0.01	°
Accuracy (absolute) (3)	Ta = 0°...50°C,	0.08	0.1	0.3	°
Tempertur drift offset			8		mV
Non-linearity			1.5		%[FS]
Cross sensitivity			0.15		%[FS]
Voltage output signal		0.3		4.7	V
Current consumption			15		mA
Power supply		4.75	5	5.25	VDC
Operation temperature range		-40		+85	°C
Storage temperature range		-40		+85	°C
Weight			20		g
Dimensions	W x D x H		45 x 45 x 14(20)		mm

(1) measurement ranges available: +/-2°, +/-5°, +/-10°, +/-15°, +/-30°

(2),(3) depend on measurement range

### Pinning

Pin	Name	Description	Type
1	Vcc	Positive power supply +5VDC	Supply, Input
2	Vref	Reference potential +2.5VDC	Output
3	GND	Ground (negative supply voltage)	Supply, Input
4	Out X	Output signal X axis	Output
5	Out Y	Output signal Y axis	Output
6	Out T	Output Signal Temperature in use	Output
7	Data	I2C like bus for EEPROM	Input/Output
8	Clock	I2C like bus for EEPROM	Input

For more details please use the product specification/ application note / instruction manual.

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

## ordering info

### PART NUMBERING

### UNIT

### SHORT DESCRIPTION

G-NSAAL-006	NS- 2/AAL2-UDD	Range +/-2°, Vcc +5 VDC, voltage output , T-signal, e <sup>2</sup> -prom
G-NSAAL-017	NS- 5/AAL2-UDD	Range +/-5°, Vcc +5 VDC, voltage output , T-signal, e <sup>2</sup> -prom
G-NSAAL-003	NS-10/AAL2-UFG	Range +/-10°, Vcc +5 VDC, voltage output
G-NSAAL-010	NS-10/AAL2-UDG	Range +/-10°, Vcc +5 VDC, voltage output , T-signal, e <sup>2</sup> -prom
G-NSAAL-018	NS-15/AAL2-UDG	Range +/-15°, Vcc +5 VDC, voltage output , T-signal, e <sup>2</sup> -prom
G-NSAAL-019	NS-30/AAL2-UDN	Range +/-30°, Vcc +5 VDC, voltage output , T-signal, e <sup>2</sup> -prom
G-NSMIS-004	Connector,cable	Connector, 8 pin, 20 cm ribbon cable for AAL-series