

44900 Series Thermistor Components

2252 Ohm to 30K Ohm
 Resistance @ 25°C
 Flight Qualified
 Interchangeability
 High Sensitivity
 Pressed Disk Key Characteristics



44900 SERIES THERMISTORS

NASA Qualified epoxy encapsulated precision interchangeable NTC thermistors for use in extended space flight applications. All parts are fully flight tested and characterized. Line re-qualified yearly per MIL-PRF-23648 requirements as specified in S311-P18 document. All S311-P18 lead options wire options available.

FEATURES

- Flight Qualified
- 2252 Ohm to 30K Ohm Resistance @ 25°C
- Interchangeability to $\pm 0.1^\circ\text{C}$
- High Sensitivity
- Thermally Conductive Epoxy Coating Exhibits <0.66% TML, <0.01% CVCM, 0.10% WVR when tested per ASTM E-

APPLICATIONS

- Extended Space Applications
- Low and Mid Range Temperature Applications
- Tight Tolerance Instrumentation
- Applications Requiring Sensing Small Changes in Temperature
- Applications with Outgassing Requirements

testing

Requalification includes the following tests referenced in MIL-PRF-23648

- Short time load
- Thermal shock
- Insulation resistance
- Resistance to soldering heat
- Low-temperature storage
- High-temperature storage
- Dissipation constant
- Thermal time constraint
- Terminal strength
- Moisture resistance
- High-temperature exposure
- Medium-impact shock
- Immersion

44900 Series Thermistor Components

product definition

	Part Number	GSFC S311-P18 Number	Basic MEAS Thermistor	Zero Power Resistance ohm at 25°C	Beta 0- 50°C (K)	Operating & Storage Temperature*	Color Code Body	End
±0.2°C Interchangeability Tolerance 0 – 70°C	44901	-01S7R6	44004	2252	3891	-55 -+ 90°C	Black	Yellow
	44903	-03S7R6	44005	3000	3891	-55-+ 90°C	Black	Green
	44905	-05S7R6	44007	5000	3891	-55 -+ 90°C	Black	Violet
	44907	-07S7R6	44006	10K	3574	-55-+ 90°C	Black	Blue
	44909	-09S7R6	44008	30K	3810	-55 -+ 90°C	Black	Gray
	44902	02S7R6	44033	2252	3891	-55 -+ 70°C	Orange	Orange
	44904	-04S7R6	44030	3000	3891	-55 -+ 70°C	Orange	Black
	44906	-06S7R6	44034	5000	3891	-55 -+ 70°C	Orange	Yellow
	44908	-08S7R6	44031	10K	3574	-55 -+ 70°C	Orange	Brown
	44910	010S7R6	44032	30K	3810	-55 -+ 70°C	Orange	Red

* Thermistors with ±0.2°C interchangeability tolerance may have short-term operating temperature excursions to 150°C
 Thermistors with ±0.1°C interchangeability tolerance may have short-term operating temperature excursions to 100°C

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

ordering info

NORTH AMERICA

Measurement Specialties, Inc.
 2670 Indian Ripple Road
 Dayton, OH 45440
 Tel: 1-937-427-1231
 Fax: 1-937-427-1640

Sales email: temperature.info.dayton@meas-spec.com

EUROPE

Measurement Specialties, Inc
 Ballybrit Business Park
 Galway Ireland
 Tel: +353-91-753238
 Fax: +353-91-770789

Sales email:
temperature.sales.emea@meas-spec.com

ASIA

Measurement Specialties (China) Ltd.
 No. 26 Langshan Road
 Shenzhen High-Tech Park (North)
 Nanshan District, Shenzhen 51807
 China
 Tel: +86 (0) 755 33305088
 Fax: +86 (0) 755 33305099

Sales email:
temperature.sales.asia@meas-spec.com