

1

2


3

4

A

A


DB25 Male



10M±10CM

23MM

DB25 Male



B

B

Configuration:

DB25M

DB25M

1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6
7	_____	7
8	_____	8
9	_____	9
10	_____	10
11	_____	11
12	_____	12
13	_____	13
14	_____	14
15	_____	15
16	_____	16
17	_____	17
18	_____	18
19	_____	19
20	_____	20
21	_____	21
22	_____	22
23	_____	23
24	_____	24
25	_____	25
Shield	_____	Shield

C

C

Material:

- 1.Cable: #28 25C+1+AL/MY (Beige PVC Jacket) O.D:6.5MM
- 2.Both connectors with normal type
- 3.Thumbscrew: #4-40UNC Type
- 4.Overall Molded with Beige PVC

Notes:

- 1.Total Length: 7M±10CM
- 2.Color: Beige
- 3.Molded Type



Description

Name :
AK164 - 10 - R
 DB25 Male-DB25 Male

D

D



THIS DRAWING IS UNPUBLISHED

© Copyright 2005 by Assmann Electronic Components All International Rights Reserved

This drawing is a controlled document for Assmann Electronics, Inc. It is subject to change and the controlling engineering organization should be contacted for the latest revision.

1

2

3

4