



Material:

- Housing: PBT+30% G.F. UL 94V-0
- Contact: Phosphor Bronze
- Color: White
- Front Shell: Brass
- Back Shell: SPCC

Plating:

- Plating: Gold 5μ"
- Shell: Nickel over all plating

Electrical:

- Current rating: 1.5A Max.
- Voltage rating: 30V Max.
- Contact resistance: 30mΩ Max.
- Insulation resistance: 1,000MΩ Min.
- Dielectric withstanding voltage: 500V AC
- Temperature range: -55°C ~ +85°C

Unit: mm



Scale	1:1						Date	Name	Title USB 1.1 DIP Connector for PCB Mount, A Female type	
TOLERANCE						Drawn	08.01.13	Wilson		
X.X	±0.3					Approved	08.01.13	Groll	ASSMANN WSW-No.	
X.XX	±0.15								A-USB-A-E-R	
X.XXX	±0.100								Drawing-No.	
DIM	TOL								rev00	
X.X°	±3.00°									
X.XX°	±1.00°	ⓐ								
X.XXX°	±0.500°	Id.	Modification	Date	Name				Replace	Sheet
									1/1	



1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@assmann.us