



Note:

- Material: Housing-polycarbonate, clear
- Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.



P1	P2
1 BLACK	1
2 RED	2
3 GREEN	3
4 YELLOW	4

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-4/4/W-5/R-R	A	1,525±20(5ft)	White	1,525-1,535mm
AT-S-26-4/4/W-7/R-R	B	2,135±30(7ft)	White	2,135-2,145mm
AT-S-26-4/4/W-10/R-R	C	3,050±60(10ft)	White	3,050-3,060mm
AT-S-26-4/4/W-12/R-R	D	3,660±60(12ft)	White	3,660-3,670mm
AT-S-26-4/4/W-14/R-R	E	4,270±60(14ft)	White	4,270-4,280mm
AT-S-26-4/4/W-25/R-R	F	7,625±100(25ft)	White	7,625-7,635mm
AT-S-26-4/4/W-50/R-R	G	15,250±150(50ft)	White	15,250-15,260mm

SEC:A-A

Unit: mm



Scale	Free				Date	Name	Title Modular cable - Reversed 4P4C 50µm, White, 5-50 feet	
TOLERANCE					Drawn	Wilson		
X.	±X				Approved	Groll	ASSMANN WSW-No.	
X.X	±X						AT-S-26-4/4/W-xx/R-R	
X.XX	±X						Drawing-No.	
DIM	TOL						rev00	
X.°	±X°						Replace	Sheet
X.X°	±X°							1/1
Angle	TOL	Id.	Modification	Date	Name			



1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@assmann.us