



Note for plug:

- Material: Housing-polycarbonate, clear.
- Terminal-0.36[.014] thick phosphor bronze.
- Thick gold in localized gold plate.
- Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

| P1 | P2 |
|----------|----|
| 1 WHITE | 1 |
| 2 BLACK | 2 |
| 3 RED | 3 |
| 4 GREEN | 4 |
| 5 YELLOW | 5 |
| 6 BLUE | 6 |

| Part Number | Drawing Number | Wire Length "L" | Jacket Color | Cut Length |
|----------------------|----------------|------------------|--------------|-----------------|
| AT-S-26-6/6/B-5/R-R | A | 1,525±20(5ft) | Black | 1,525-1,535mm |
| AT-S-26-6/6/B-7/R-R | B | 2,135±30(7ft) | Black | 2,135-2,145mm |
| AT-S-26-6/6/B-10/R-R | C | 3,050±60(10ft) | Black | 3,050-3,060mm |
| AT-S-26-6/6/B-12/R-R | D | 3,660±60(12ft) | Black | 3,660-3,670mm |
| AT-S-26-6/6/B-14/R-R | E | 4,270±60(14ft) | Black | 4,270-4,280mm |
| AT-S-26-6/6/B-25/R-R | F | 7,625±100(25ft) | Black | 7,625-7,635mm |
| AT-S-26-6/6/B-50/R-R | G | 15,250±150(50ft) | Black | 15,250-15,260mm |

Unit: mm



| Scale | Free | | | | | Date | Name | Title |
|-----------|------|-----|--------------|------|------|-------------------|----------|--------|
| TOLERANCE | | | | | | Drawn | 27.06.13 | Wilson |
| X. | ±X | | | | | Approved | 27.06.13 | Groll |
| X.X | ±X | | | | | | | |
| X.XX | ±X | | | | | | | |
| DIM | TOL | | | | | | | |
| X.° | ±X° | | | | | | | |
| X.X° | ±X° | | | | | | | |
| Angle | TOL | Id. | Modification | Date | Name | Replace Sheet 1/1 | | |

| Title | |
|--|-----------|
| Modular cable - Straight/Reversed 6P6C 50µ", 26AWG, Black, 5-50 feet | |
| ASSMANN WSW-No. | |
| AT-S-26-6/6/B-xx/R-R | |
| Drawing-No. | rev00 |
| Replace | Sheet 1/1 |



1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
 Toll Free: 1-877-277-6266 • Email: info@assmann.us