

Material
 Item a Clamp : Brass(CuZn) Ni plated
 Item b Terminal screw: Steel Zinc plating "-" slot type
 Item c Female contact : PhBz(CuZn)Tin plated
 Item d Terminal housing: Thermoplastic (UL94V-0) ,Green

Electrical cULus
 Voltage rating: 300V
 Current rating: 10A
 Wire range:
 Solid wire(AWG): 16-28
 Stranded wire(AWG): 16-28
 Torque(Lb-In): 1.7
 Screw: M2
 Wire strip length: 5-6mm
 Withstanding Voltage: 1.6KV
 Operating temperature: -40°C to +115°C
 Safety approval: cULus


DIMENSION

L	Nx3,5
P	(N-1)x3,5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
4p-6p	±0.15	±0.15
7p-12p	±0.20	±0.20
13p-24p	±0.30	±0.30

RoHS compliant

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	30.11.2006	Hellwig
X.	±0.50					Approved	20.04.2010	Hellwig
X.X	±0.30							
X.XX	±0.10							
DIM	TOL	②	Update	20.04.2010	Alex			
X.°	±1°	①	Drawn	30.11.2006	Hellwig			
Angle	TOL	Id.	Modification	Date	Name	Replace		Sheet

ASSMANN WSW-No.
A-TB350-THxx

Drawing-No.
ASS 1150 CO rev02