

	1	2	3	4	5	6	7																																								
A	<p>Material</p> <p>Terminal body (metal housing): Brass(CuZn) Insulator (housing): Thermoplastic (UL94V-0), Green Wire guard: PhBz, Tin plated Terminal screw :Steel Zinc plating"-slot type Electrical cULus/ CSA /VDE Voltage rating: 300VAC/125VAC/300VAC Current rating: 10A/8A/10.5A Wire range: 1.5mm² Solid wire(AWG): 16-26/16-26 Stranded wire(AWG): 6-26/16-26 Torque: 3Lb-In / 3.5kgf.cm / 0.2N.m Screw: M2 With strip length:6-7mm Withstanding Voltage: 1.6KV/1.6KV/2.5KV Operating temperature: -30°C to +105°C Safety Approval: </p>																																														
B																																															
C																																															
D																																															
E																																															
F	<p>N= NUMBER OF CONTACTS</p>																																														
G	<p>RoHS compliant</p> <table border="1"> <tr> <td>Scale</td> <td>1:1</td> </tr> <tr> <td>TOLERANCE</td> <td></td> </tr> <tr> <td>X.</td> <td>±0.50</td> </tr> <tr> <td>X.X</td> <td>±0.30</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> </tr> <tr> <td>DIM TOL</td> <td></td> </tr> <tr> <td>X.°</td> <td>±1°</td> </tr> <tr> <td>Angle TOL</td> <td></td> </tr> </table> <table border="1"> <tr> <td>Customer-No.</td> <td colspan="2"></td> </tr> <tr> <td>Name</td> <td>Dean</td> <td>Date</td> </tr> <tr> <td>Date</td> <td>10.12.2009</td> <td>10.12.2009</td> </tr> <tr> <td>Approved</td> <td>Hellwig</td> <td></td> </tr> <tr> <td colspan="3"> </td> </tr> <tr> <td>ASSMANN WSW-No.</td> <td colspan="2">A-TB350-TJxxU</td> </tr> <tr> <td>Drawing-No.</td> <td colspan="2">ASS 3822 CO rev01</td> </tr> <tr> <td>Replace</td> <td colspan="2">Sheet</td> </tr> </table>							Scale	1:1	TOLERANCE		X.	±0.50	X.X	±0.30	X.XX	±0.10	DIM TOL		X.°	±1°	Angle TOL		Customer-No.			Name	Dean	Date	Date	10.12.2009	10.12.2009	Approved	Hellwig					ASSMANN WSW-No.	A-TB350-TJxxU		Drawing-No.	ASS 3822 CO rev01		Replace	Sheet	
Scale	1:1																																														
TOLERANCE																																															
X.	±0.50																																														
X.X	±0.30																																														
X.XX	±0.10																																														
DIM TOL																																															
X.°	±1°																																														
Angle TOL																																															
Customer-No.																																															
Name	Dean	Date																																													
Date	10.12.2009	10.12.2009																																													
Approved	Hellwig																																														
ASSMANN WSW-No.	A-TB350-TJxxU																																														
Drawing-No.	ASS 3822 CO rev01																																														
Replace	Sheet																																														
H	<table border="1"> <tr> <td>Drawn</td> <td>Dean</td> <td>Date</td> <td>10.12.2009</td> </tr> <tr> <td>Modification</td> <td></td> <td>Name</td> <td>Dean</td> </tr> </table>							Drawn	Dean	Date	10.12.2009	Modification		Name	Dean																																
Drawn	Dean	Date	10.12.2009																																												
Modification		Name	Dean																																												
	1	2	3	4	5	6	7																																								