



**Material**

Terminal body  
 (contact pin): Brass(CuZn) Tin plated  
 Insulator (housing): Thermoplastic (UL94V-0),Green

**Electrical cULus/CSA/VDE**

Voltage rating: 300VAC/125VAC/125VAC  
 Current rating: 10A/8A/10.5A  
 Wire range:  
 Solid wire(AWG):  
 Stranded wire(AWG):  
 Withstanding Voltage: 1.6KV/1.6KV/2.5KV  
 Operating temperature: -30°C to +105°C  
 Soldering temperature: 250°C±10°C/5 Sec  
 Safety Approval:

N= NUMBER OF CONTACTS

**RoHS compliant**

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	10.12.2009	Dean	ASSMANN WSW-No. <b>A-TB381-OQxxCV</b>
X.	±0.50					Approved	10.12.2009	Hellwig	
X.X	±0.30								
X.XX	±0.10								
DIM	TOL								Drawing-No.
X.°	±1°								<b>ASS 3829 CO</b>
		①	Drawn	10.12.2009	Dean				rev01
Angle	TOL	Id.	Modification	Date	Name			Replace	Sheet



**ASS 3829 CO** rev01

Replace Sheet