

1

2

3

4

5

6

7

A

B

C

D

E



F

G

H

Material

Item a Male contact pin: Copper Tin plated
 Item b Terminal (housing): Thermoplastic (UL94V-0) , GREEN

Electrical cULus/VDE
 Voltage rating: 300V/300V
 Current rating: 8A/10A
 Withstanding Voltage: 1.6KV/2.5KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval: cULus  

RECOMMENDER PCB LAYOUT


DIMENSION

L	(N-1)x3.5+4.9
P	(N-1)x3.5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
2p-6p	±0.15	±0.15
7p-12p	±0.20	±0.20
13p-18p	±0.25	±0.25
19p-24p	±0.30	±0.30

RoHS compliant

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	19.04.2010	
X.	±0.50					Approved	19.04.2010	Hellwig
X.X	±0.30							
X.XX	±0.10							
DIM	TOL							Drawing-No.
X.°	±1°							ASSMANN WSW-No. A-TB350-VKxx
		©	Drawn	19.04.2010	Alex			ASS 4118 CO
Angle	TOL	Id.	Modification	Date	Name			Replace

Customer-No.

ASSMANN WSW-No.
A-TB350-VKxx

Drawing-No.

ASS 4118 CO

rev00

Replace

Sheet

1

2

3

4

5

6

7

A

B

C

D

E

F

G

H