REV.	DATE	DESCRIPTION
A	01/30/04	UPDATE DRAWING FORMAT



RECOMMENDED CABLE
STRIPPING DIMENSIONS



NOTE:

1. CRIMPED FERRULE
   HEX CRIMP SIZE .128”
2. CRIMPED CONTACT PIN
   SQ. CRIMP SIZE 0.7(mm)

8				
7				
6				
5				
4	FERRULE	COPPER	NEXCOTE	1
3	CONTACT PIN	PHOS. BRONZE	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY	BRASS	NEXCOTE	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.020 – .315 = ± 0.007”
.315 – 1.180 = ± 0.015”
1.180 – 4.724 = ± 0.020”

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	01/30/04
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/172/172173.DWG

Amphenol Connex

PART DESCRIPTION
N PANEL CRIMP JACK
(FOR RG–174/U,188A/U,316/U)

PART NO. 172173

DWG. NO.	REV.	SIZE	SCALE
172173.DWG	A	A	NA