


REV.	DATE	DESCRIPTION
D	04/11/97	ADD $\phi 15.75$ BODY DIMENSION
E	01/19/98	CHANGE TO $\phi 15.57$ BODY DIMENSION
F	03/19/05	UPDATE DRAWING FORMAT/ CHANGE STRIPPING DIMS
G	02/08/06	UPDATE ITEM (5) TO FLAT WASHER.
H	03/20/07	REVISE PLATING TO NEXCOTE



NOTE:

- CONTACT PIN TO SOLDER
- MAX. PANEL THICKNESS = 6.5mm

12				
11	HEX NUT	BRASS	NEXCOTE	1
10	WASHER	BRASS	NEXCOTE	1
9	TOP HAT	BRASS	NEXCOTE	1
8	INSULATOR	TEFLON	NATURAL	1
7	CONTACT PIN	BRASS	GOLD	1
6	HEX NUT	BRASS	NEXCOTE	1
5	FLAT WASHER	BRASS	NEXCOTE	1
4	GASKET	SILICONE	RED	1
3	CONTACT PIN	BER. COPPER	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY	BRASS	NEXCOTE	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
 0.5 - 8mm ± 0.20 mm
 8 - 30mm ± 0.40 mm
 30 - 120mm ± 0.50 mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
 .020 - .315 = ± 0.007 "
 .315 - 1.180 = ± 0.015 "
 1.180 - 4.724 = ± 0.020 "

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	03/20/07
CHECKED	
ISSUED	
SHEET 1 OF 1	
CAD FILE	C:/172/172143.DWG

Amphenol Connex

N BULKHEAD CLAMP JACK
(FOR RG-174/U,188A/U,316/U)

172143

PART DESCRIPTION			
N BULKHEAD CLAMP JACK (FOR RG-174/U,188A/U,316/U)			
PART NO.			
172143			
DWG. NO.	REV.	SIZE	SCALE
172143.DWG	H	A	NA