REV.	DATE	DESCRIPTION
NC	04/25/06	INITIAL RELEASE







RECOMMENDED
CABLE STRIPPING DIM'S



NOTE:
1. CRIMPED FERRULE – HEX CRIMP SIZE .429"

	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5	COVER	BRASS	NICKEL	1
4	FERRULE	COPPER	NICKEL	1
3	CONTACT PIN	PHOS. BRONZE	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	BODY	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	04/25/06
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/122/122416RP.DWG

Amphenol Connex

PART DESCRIPTION
TNC REVERSE POLARITY R/A CRIMP PLUG
(FOR RG-8/U, 213/U, LMR400, BELDEN 9913,9914)

PART NO. 122416RP

DWG. NO.	REV.	SIZE	SCALE
122416RP.DWG	NC	A	NA